

# EDV Euro twist-on connection 31430

CE  
6/2022

## Areas of application:

For the installation of pipes on all major cable trays with slotted holes with a sheet thickness of 0.5 to 1.1 mm.

## Installation Guide:

EC in combination with EDV:

- Click the EC to the EDV
- Put the EC with EDV into the long hole of the cable tray.
- Lock this combination by twisting a 45°-turn
- The EC clamp is adjustable after mounting to the EDV
- Push the pipe into the EC clamp
- Cables can be attached to the EDV with a cable tie



## Product details:

Colour	light grey
Content pack/box	200 / 3.000
Metal thickness range	0,5 - 1,1 mm

## Mounting and usage instructions:

Simply connect the EC Euro Clips to the EDV and install it in a slotted hole of the cable route. The ESV can be mounted sidewise or on the underside of a cable route. Attention: Working Temperature at min. + 5° C

## Product benefits/properties:

The ideal way to relieve full cable routes, is a separate cable routing on / beside / under the cable route (for additional cables, data cables, etc.). The conduit itself acts as an electromagnetic divider.

- Applicable for all crossings on the cable route underside
- Several Euro-clips can be attached with only one EDV - this results in saved time and money.
- Compatible with all Schnabl Euro Clips (EC 16, EC 20, EC 32, EC 40, EC 50)
- Fast and easy installation
- Reliable fastening - tensile strength 40 kg

## Technical data:

Material	PA 6, UV stabilised Temperature range: -20 °C up to +85 °C silicon-free halogen-free
----------	---

Weight per piece 0,80 g

GTIN (EAN) 9 008439 414307



Ideal for fixing pipes to all conventional cable conduits with slotted holes.



Schnabl Stecktechnik GmbH, Bahnhofplatz 1, po box 63, 3100 St. Pölten, Austria  
Telephone +43 2742 22167-0. office@schnabl.works. www.schnabl.works

