

# UNIVERSAL RESTRAINT CLIP, STEEL, EG, #12, #18, #36 BRACE, 21 MM HOLE

## **CATALOG NUMBER**

# CSBURC34



# **CERTIFICATIONS**









## **FEATURES**

Attaches cable brace to structure

Meets CEN/TS 17551:2021 requirements for Seismic Sway Bracing

#### **PRODUCT ATTRIBUTES**

Article Number: 402519

Material: Steel

Finish: Electrogalvanized

Brace Size: #12; #18; #36

Hole Size: 21 mm

Thickness: 4.27 mm

UL Listed Load: 7120 N


# **ADDITIONAL PRODUCT DETAILS**

Brace member is not included.

Mount to the structure using the center hole. Loop cable through the holes in the bent tabs and swage in place.

UL Loads		
Part Number	Brace Member	Load Rating
CSBURC38	CSB12CBL	1859 N
	CSB18CBL	3434 N
	CSB36CBL	8492 N
CSBURC12	CSB12CBL	1859 N
	CSB18CBL	3434 N
	CSB36CBL	8492 N
CSBURC58	CSB12CBL	1859 N
	CSB18CBL	3434 N
	CSB36CBL	8492 N
CSBURC34	CSB12CBL	1859 N
	CSB18CBL	3434 N
	CSB36CBL	8492 N
CSBURC78	CSB12CBL	1859 N
	CSB18CBL	3434 N
	CSB36CBL	8492 N

## **DIAGRAMS**



## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

#### **North America**

+1.800.753.9221

Option 1 – Customer Care

Option 2 - Technical Support

**Europe** 

Netherlands: +31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF

nVent.com
TRACER