

0023300	DATA SHEET	
valid from: 14.05.2024	ÖLFLEX® PETRO FD 865 CP	

Application

ÖLFLEX® PETRO FD 865 CP cables are oil-resistant control cables with an outer sheath of special polymer compound for high flexible use and fixed installation under medium mechanical load conditions. They are also suitable for use in dry, damp or wet areas. They are suitable for outdoor use if the indicated temperature range is observed.

ÖLFLEX® PETRO FD 865 CP cables are resistant to oil and drilling fluids according to NEK TS 606:2022 (Oil & MUD) as well as IEC 60092-360 and at room temperature widely resistant to acids and alkalis.

The outer sheath withstands high mechanical stresses, in particular abrasion and dragging. It is also cut proof and resists microbes and hydrolysis. They are especially suitable for increased requirements (Extended Line) in power chains and in permanently moved machine parts. They are suitable for linear, automated movements. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

All materials used are halogen-free. The screening braid protects against interference from electrical fields.

Application range: Power chains or moving machine parts, on- and offshore applications e.g. offshore drilling platform, drillship; machine tools and transfer lines, mechanical engineering, construction machinery, assembly lines, production lines, in all kinds of machines.

Design

Design	based on EN 50525-2-21 and EN 50525-2-5 1
Certification	DNV (Certificate-No. TAE000031E)
Conductor	extra fine wire strands of bare copper acc. to IEC 60228 resp. EN 60228, Class 6
Insulation	TPE (Thermoplastic Elastomer)
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor black cores with white numbers acc. to EN 50334
Stranding	cores are stranded in layers
Wrapping	non-woven wrapping
Inner sheath	TPE (Thermoplastic Elastomer)
Screen	braid of tinned copper wires, coverage = 85% (nominal value)
Outer sheath	Special polymer compound colour: Black, similar RAL 9005

Electrical properties at 20 °C

Specific volume resistivity	> 20 G Ω x cm
Nominal voltage	U ₀ / U : 300 / 500 V
Test voltage	core / core: 3000 V AC core / screen: 3000 V AC

Mechanical and thermal properties

Minimum bending radius	flexing: up from 7.5 x outer diameter fixed installation: 4 x outer diameter
Temperature range	flexing: -50 °C up to +80 °C max. conductor temp. fixed installation: -60 °C up to +80 °C max. conductor temp.
Bending cycles and power chain operation parameters	See Selection Table A2-1 in the appendix of our online catalogue For use in power chains: Please comply with assembly guideline Appendix T3
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2
Halogen free	acc. to EN 60754-1
UV resistance	Acc. to EN 50525-1 cables with black sheath are suitable for permanent outdoor use. acc. to EN 50618 acc. to EN 50620 acc. to EN ISO 4892-2-2013, method A (change of colour allowed)
Oil resistance	acc. to EN 50363-10-2
MUD resistance	acc. to NEK TS 606: 2022 and IEC 60092-360
Water-resistance	Salt water resistance acc. to UL 1309

Tests acc. to IEC 60811, EN 60811, EN 50395

Creator: HESC / PDC	Document: DB0023300EN	Page 1 of 2
Released: ALTE / PDC	Version: 08	

0023300	DATA SHEET	
valid from: 14.05.2024	ÖLFLEX® PETRO FD 865 CP	

General requirements

These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive).
 These cables (see www.lappkabel.com/cpr) are classified in accordance with the
 EU-Regulation no. 305/2011 (CPR).

Environmental information

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: HESC / PDC Released: ALTE / PDC	Document: DB0023300EN Version: 08	Page 2 of 2
---	--------------------------------------	-------------