



DALI
system

 [V] 220-240 AC	 [Hz] 50	 ≥30000	 50000	 elliptic ≤3x Macdon	 Ra 80	 SMD
 DALI		 IP 65		 IK 08		
 0,5÷2,5	 0,5m					



FTD1200 28W-840-OPL

		 [W]	 Tc [K]	 TYPE	 [°]	 [lm]	 lm W	 [mm]	 °C
FTD1200 28W-840-OPL	28854	28	4000	opálový	X130/Y110	4100	146	1180	-25÷40
FTD1200 28W-840-RYF	28855	28	4000	drážkovaný	X115/Y105	4500	161	1180	-25÷40
FTD1200 28W-840-INT	28856	28	4000	prizmatický, s úzkým paprskem	X70/Y95	4300	154	1180	-25÷40
FTD1200 28W-840-ASY	28857	28	4000	prizmatický, asymetrický	X75/Y95	4300	154	1180	-25÷40



FTD1200 28W-840-OPL




FTD1200 28W-840-RYF




FTD1200 28W-840-INT




FTD1200 28W-840-ASY




FTD1200 28W-840-OPL



FTD1200 28W-840-RYF



FTD1200 28W-840-INT



FTD1200 28W-840-ASY

Dokument vytvořen: 19.07.2025, 13:11

Změna technický parametrů vyhrazena. Informace uvedené v tomto dokumentu nejsou právně závazné.

Fotometrie: výsledky získané během testování konkrétního exempláře.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

