

UBK Universal fastener for cable trays

31750

CE 2/2024

Areas of application:

For the secure attachment of lights, presence and smoke detectors as well as junction boxes on all common cable trays with oval holes with a sheet thickness of 0.5 to 1.1 mm.

Installation Guide:

The assembly of the UBK is simple:

- Insert the UBK into the slot in the cable tray.
- Lock the combination with the cable tray by turning it 45°.
- Insert the mounting hole of the attachment through the retainer tab of the UBK and let it snap into place with the lock.
- Finished!

Product details:

Colour	light grey
Content pack/box	100 / 2.000
Suitable sheet thickness	0,5 - 1,1 mm

Mounting and usage instructions:

The attachment can be easily connected to the UBK and attached to an oval hole in the cable tray. Installation can be done on the sides or below the cable tray.

Product benefits/properties:

The UBK offers an ideal solution for simple and quick use of the existing cable route as an installation location.

- Saves time and money.
- Reliable hold with a tensile strength of 2 kg.

Technical data:

Material	PA 6 H0, silicon-free Temperature range: -20 °C up to +85 °C silicon-free halogen-free
----------	--

Weight per piece 1,09 g

Breaking load Tightening torque: 20 kg (Tightening torques are averages and can vary due to different influences.)

GTIN (EAN)



Schnabl Stecktechnik GmbH, Bahnhofplatz 1, po box 63, 3100 St. Pölten, Austria
Telephone +43 2742 22167-0. office@schnabl.works. www.schnabl.works

