



■ Features :


- 2:1 wide input range
- 4:1 wide input range(option)
- 1000VDC I/O isolation
- 3000VDC I/O isolation(option)
- Built-in EMI filter
- Protections: Short circuit / Overload
- Cooling by free air convection
- Six-sided shield metal case
- 100% burn-in test
- Low cost / High reliability
- Approvals: FCC / CE
- 2 years warranty


SPECIFICATION

ORDER NO.	SLW05A-05	SLW05B-05	SLW05C-05	SLW05A-09	SLW05B-09	SLW05C-09	SLW05A-12	SLW05B-12	SLW05C-12	SLW05A-15	SLW05B-15	SLW05C-15
OUTPUT	DC VOLTAGE	5V		9V			12V			15V		
	CURRENT RANGE	100 ~ 1000mA		55.6 ~ 556mA			41.7 ~ 417mA			33.3 ~ 333mA		
	RATED POWER	5W										
	VOLTAGE ACCURACY	±2.0%										
	RIPPLE & NOISE (max.) Note.2	50mVp-p		60mVp-p			60mVp-p			60mVp-p		
	LINE REGULATION Note.3	±0.2%										
	LOAD REGULATION Note.4	±0.5%										
INPUT	SWITCHING FREQUENCY	50KHz min.										
	VOLTAGE RANGE	A: 9 ~ 18VDC	B: 18 ~ 36VDC	C: 36 ~ 72VDC								
	EFFICIENCY (Typ.)	75%	77%	77%	80%	80%	83%	80%	80%	83%	81%	81%
	DC CURRENT	Full load	A: 556mA	B: 270mA	C: 135mA							
		No load	A: 33mA	B: 16mA	C: 10mA							
PROTECTION (Note. 5)	FILTER	Pi network										
	PROTECTION	Fuse recommended										
	OVER CURRENT	160 ~ 250% rated output power										
		Protection type : Hiccup mode, recovers automatically after fault condition is removed										
ENVIRONMENT	SHORT CIRCUIT	All output equipped with short circuit										
		Protection type : Hiccup mode, recovers automatically after fault condition is removed										
	WORKING TEMP.	-25 ~ +71°C (Refer to output load derating curve)										
	WORKING HUMIDITY	20% ~ 90% RH non-condensing										
	STORAGE TEMP., HUMIDITY	-25 ~ +105°C, 10 ~ 95% RH										
SAFETY & EMC	TEMP. COEFFICIENT	±0.03% / °C (0 ~ 50°C)										
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes										
	WITHSTAND VOLTAGE	I/P-O/P:1KVDC										
	ISOLATION RESISTANCE	I/P-O/P: 100M Ohms / 500VDC / 25°C / 70% RH										
OTHERS	EMI CONDUCTION & RADIATION	Compliance to EN55022 Class B, FCC part 15 Class B										
	EMS IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,8, light industry level, criteria A										
	MTBF	800khrs min. MIL-HDBK-217F(25°C)										
DIMENSION	DIMENSION	50.8*25.4*11.27mm or 2*1*0.44" inch (L*W*H)										
	WEIGHT	32g										

Mechanical Specification

Pin Configuration

Pin no.	Output Single
1	+Vin
2	-Vin
3	+Vout
4	No Pin
5	-Vout

Derating Curve

NOTE

1. All parameters are specified at normal input, rated load, 25°C 70% RH ambient.
2. Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
3. Line regulation is measured from low line to high line at rated load.
4. Load regulation is measured from 10% to 100% rated load.
5. Please prevent the converter from operating in overload or short circuit condition for more than 30 seconds.