



■ Features :

- Universal AC input/Full range
- Protections: Short circuit / Overload / Over voltage / Battery polarity protections (by fuse)
- Cooling by free air convection
- LED indicator for power on
- No load power consumption <0.75W
- 100% full load burn-in test
- 2 years warranty




SPECIFICATION


MODEL	SCP-50-12	SCP-50-24
OUTPUT	DC VOLTAGE	13.8V
	RATED CURRENT	3.6A
	CURRENT RANGE	0 ~ 3.6A
	PEAK 5S Note.6	4.3A
	RATED POWER	49.7W
	RIPPLE & NOISE (max.) Note.2	120mVp-p
	VOLTAGE ADJ. RANGE	+15,-5%
	VOLTAGE TOLERANCE Note.3	±2.0%
	LINE REGULATION Note.4	±1.0%
	LOAD REGULATION Note.5	±2.0%
SETUP, RISE TIME		500ms, 30ms/230VAC 1200ms, 30ms/115VAC at full load
HOLD UP TIME (Typ.)		50ms/230VAC 16ms/115VAC at full load
INPUT	VOLTAGE RANGE	85 ~ 264VAC 120 ~ 370VDC
	FREQUENCY RANGE	47 ~ 63Hz
	EFFICIENCY(Typ.)	81% 85%
	AC CURRENT (Typ.)	1.1A/115VAC 0.65A/230VAC
	INRUSH CURRENT (Typ.)	COLD START 45A
FUNCTION	LEAKAGE CURRENT	<2mA / 240VAC
	TEMP. COMPENSATION	By NTC (not provide with the power supply)
PROTECTION	OUTPUT VOLTAGE SENSOR	L=output voltage $^{+0.7}_{-0}$ V
	OVERLOAD	4.3 ~ 5.8A rated output power 2.2 ~ 2.9A rated output power
	Protection type : Hiccup mode, recovers automatically after fault condition is removed	
	OVER VOLTAGE	16.6 ~ 19.3V 33.1 ~ 38.5V
ENVIRONMENT	Protection type : Shut down o/p voltage, re-power on to recover	
	WORKING TEMP.	-20 ~ +60°C (Refer to output load derating curve)
	WORKING HUMIDITY	20 ~ 90% RH non-condensing
	STORAGE TEMP., HUMIDITY	-40 ~ +85°C, 10 ~ 95% RH
	TEMP. COEFFICIENT	±0.03%/°C (0 ~ 45°C)
SAFETY & EMC (Note 7)	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes
	SAFETY STANDARDS	UL60950-1, CB(IEC60950-1) approved
	WITHSTAND VOLTAGE	I/P-O/P:3KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC
	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25°C / 70% RH
	EMI CONDUCTION & RADIATION	Compliance to EN55022 (CISPR22) Class B
	HARMONIC CURRENT	Compliance to EN61000-3-2,-3
OTHERS	EMS IMMUNITY	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11, ENV50204, EN55024, EN61000-6-1, light industry level, criteria A
	MTBF	495.7K hrs min. MIL-HDBK-217F (25°C)
	DIMENSION	129*98*38mm (L*W*H)
NOTE	PACKING	0.45Kg; 30pcs/14.5Kg/0.95CUFT
1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. Line regulation is measured from low line to high line at rated load. 5. Load regulation is measured from 0% to 100% rated load. 6. 33% Duty cycle maximum within every 15 seconds. Average output power should not exceed the rated power. 7. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.		

■ Mechanical Specification


Case No. 903 Unit:mm




■ Block Diagram



■ Derating Curve



■ Output Derating VS Input Voltage



■ Function Description**1.B+,B-**

Connect the battery : B+ connected to battery positive.
B- connected to battery negative.

2.L

Output voltage detection, detection output voltage or battery voltage (if battery is used).
L=output voltage $^{+0.7}_{-0}$ V.

3.+V,-V

Output voltage. Can't connect the battery.

4.CN2

Temperature sensor can be connected to the unit to allow temperature compensation of the charging voltage.

If the sensor is not used, the charger still works normally.

Reference example:

Connect 100K Ω Thermistor(THINKING) on NTC. Adjust VR to cause the output voltage is normally voltage. The output voltage will change along with the temperature change.

	Ta :0°C	Ta :25°C	Ta :50°C
SCP-50-12	14.4 \pm 0.2V	13.8 \pm 0.1V	13.2 \pm 0.2V
SCP-50-24	29.3 \pm 0.4V	27.6 \pm 0.2V	26.4 \pm 0.4V

