



## ■ Features :

- High efficiency 90% and low power dissipation
- 150% peak load capability
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Cooling by free air convection
- Can be installed on DIN rail TS-35/7.5 or 15
- UL 508 (industrial control equipment) approved
- EN61000-6-2(EN50082-2) industrial immunity level
- 100% full load burn-in test
- 3 years warranty




CB CE

## SPECIFICATION

MODEL	SDR-75-12	SDR-75-24	SDR-75-48
OUTPUT	DC VOLTAGE	12V	24V
	RATED CURRENT	6.3A	3.2A
	CURRENT RANGE	0 ~ 6.3A	0 ~ 3.2A
	RATED POWER	75.6W	76.8W
	PEAK CURRENT	9.375A	4.69A
	PEAK POWER Note.6	112.5W (3 sec.)	
	RIPPLE & NOISE (max.) Note.2	100mVp-p	100mVp-p
	VOLTAGE ADJ. RANGE	12 ~ 14V	24 ~ 28V
	VOLTAGE TOLERANCE Note.3	± 1.0%	± 1.0%
	LINE REGULATION	± 0.5%	± 0.5%
INPUT	LOAD REGULATION	± 1.0%	± 1.0%
	SETUP, RISE TIME	1500ms, 60ms/230VAC	3000ms, 60ms/115VAC at full load
	HOLD UP TIME (Typ.)	80ms/230VAC	20ms/115VAC at full load
	VOLTAGE RANGE Note.7	88 ~ 264VAC	124 ~ 370VDC [DC input operation possible by connecting AC/L(+),AC/N(-)]
	FREQUENCY RANGE	47 ~ 63Hz	
PROTECTION	EFFICIENCY (Typ.)	88.5%	89%
	AC CURRENT (Typ.)	1.4A/115VAC	0.85A/230VAC
	INRUSH CURRENT (Typ.)	30A/115VAC	50A/230VAC
	LEAKAGE CURRENT	<1mA / 240VAC	
	OVERLOAD	Normally works within 110 ~ 150% rated output power for more than 3 seconds and then shut down o/p voltage, re-power on to recover 150 ~ 170% rated power, constant current limiting with auto-recovery within 3 seconds, and then shut down o/p voltage after 3 seconds, re-power on to recover	
	OVER VOLTAGE	14 ~ 17V	29 ~ 33V
ENVIRONMENT	OVER TEMPERATURE	Protection type : Shut down o/p voltage, re-power on to recover	
		100°C ± 10°C (RTH2) detect on main of power transistor	
		Protection type : Shut down o/p voltage, re-power on to recover after temperature goes down	
	WORKING TEMP.	-30 ~ +70°C (Refer to "Derating Curve")	
	WORKING HUMIDITY	20 ~ 95% RH non-condensing	
SAFETY & EMC (Note 4)	STORAGE TEMP., HUMIDITY	-40 ~ +85°C, 10 ~ 95% RH	
	TEMP. COEFFICIENT	± 0.03%/°C (0 ~ 60°C)	
	VIBRATION	Component:10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes; Mounting: Compliance to IEC60068-2-6	
	SAFETY STANDARDS	UL508, TUV EN60950-1 approved, design refer to GL	
	WITHSTAND VOLTAGE	I/P-O/P:3KVAC I/P-FG:2KVAC O/P-FG:0.5KVAC	
OTHERS	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:>100M Ohms / 500VDC / 25°C / 70% RH	
	EMC EMISSION	Compliance to EN55022 (CISPR22), EN61204-3 Class B, EN61000-3-2,-3	
	EMC IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,8,11, EN55024, EN61000-6-2 (EN50082-2), EN61204-3, heavy industry level, criteria A, SEMI F47 approved	
NOTE	MTBF	481.9K hrs min. MIL-HDBK-217F (25°C)	
	DIMENSION	32*125.2*102mm (W*H*D)	
	PACKING	0.51Kg; 28pcs/15.3Kg/1.22CUFT	
1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives. 5. Installation clearances : 40mm on top, 20mm on the bottom, 5mm on the left and right side are recommended when loaded permanently with full power. In case the adjacent device is a heat source, 15mm clearance is recommended. 6. 3 seconds max., please refer to peak loading curves. 7. Derating may be needed under low input voltage. Please check the derating curve for more details.			


## ■ Mechanical Specification



Case No. Unit:mm



## ■ Block Diagram

fosc : 85KHz



**■ Peak Loading**

**■ Derating Curve**

**■ Output derating VS input voltage**
