

61802180	<b>DATA SHEET</b>	
Valid from: 23.02.2024	<b>SILVYN® US-AS</b>	

SILVYN® US-AS is an inner- / end sleeve for the installing form protection conduits on the gland SILVYN® US or as an end sleeve to prevent cable from being damaged, when there is no gland installation.




**Material:** Nickel plated brass

**Technical features**

Nominal size: NW 10 up to NW 56  
 Temperature range: -40°C up to +250°C

**Suitable conduits:** SILVYN® AS

**Suitable gland:** SILVYN® US  
 SILVYN® US-M



**Dimension table:**

Part No.	Nominal size	Conduit diameter mm		Diameter C mm
		Innen	Außen	
61802180	10	8,0	10,0	6,5
61802190	14	11,0	14,0	10,0
61802200	17	14,0	17,0	12,5
61802210	19	16,0	19,0	14,5
61802220	21	18,0	21,0	16,5
61802230	27	23,0	27,0	21,5
61802240	36	31,0	36,0	29,5
61802250	45	40,0	45,0	38,0
61802270	56	51,0	56,0	49,0
For SILVYN® LAPPGRAFF				
61802191	14	12	14	10,5
61802231	27	24	27	22,5

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: MAU1 /PDP Released: DAMU1/PDP	Document: DB61802180EN Version: 05	Page 1 of 1
---	---------------------------------------	-------------