

0012452	DATA SHEET	
valid from: 30.01.2026	ÖLFLEX® 540 P 300/500 V	

Application

ÖLFLEX® 540 P cables are oil-resistant connecting cables with an insulation of TPE and an outer sheath of Polyurethane for flexible use and fixed installation under increased mechanical load conditions. They are also suitable for use in dry, damp or wet areas. They are suitable for outdoor use if the indicated temperature range is observed. They are suitable for constant use in fresh water to a depth of 10 m and at a maximum water temperature of 40°C acc. to EN 50565-2.

They are suitable for occasional, non-automated movements. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

ÖLFLEX® 540 P cables are increased resistant to oils and at room temperature largely resistant to acids and alkalis. The outer sheath withstands high mechanical stresses, in particular abrasion and dragging. It is also cut proof and resists microbes and hydrolysis. All materials used are halogen-free.

Application range:

Construction machinery, building sites, camping sites, stage application, agricultural equipment, industrial machinery, machine tools and submersible pumps.

Design

Design	based on standard EN 50525-2-21
Certification	◁ VDE-REG 6583 ▷
Conductor	fine wire strands of tinned copper acc. to IEC 60228 resp. EN IEC 60228, class 5
Insulation	Thermoplastic elastomer (TPE-V)
Core identification code	up to 5 cores coloured acc. to HD 308 S2 resp. VDE 0293-308 more than 5 cores: black cores with white numbers with GN/YE ground conductor acc. to EN 50334
Outer sheath	TPU Polyurethane compound acc. to EN 50363-10-2 colour: yellow, similar RAL 1016

Electrical properties at 20 °C

Nominal voltage	EN U ₀ / U: 300/500 V
Test voltage	3000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 10 x outer diameter fixed installation: 4 x outer diameter
Temperature range	occasional flexing: -40 °C up to +90 °C max. conductor temperature fixed installation: -50 °C up to +90 °C max. conductor temperature
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2
Halogen free	acc. to IEC 60754-1 resp. EN 60754-1
UV resistance	acc. to EN 50618 acc. to EN 50620 acc. to EN ISO 4892-2, method A (change of colour allowed)
Oil resistance	acc. to EN 50363-10-2
MUD resistance	acc. to IEC 60092-360
Water-resistance	acc. to EN 50525-2-21, Annex D + E

Tests

acc. to IEC 60811 resp. EN 60811, EN 50395, EN 50396

General requirements

These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)

Environmental information

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: SESC / PDC	Document: DB0012452EN	Page 1 of 1
Released: ALTE / PDC	Version: 11	