

|                           |                                                                          |                                                                                     |
|---------------------------|--------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 75009713                  | <b>DATA SHEET</b>                                                        |  |
| Valid from:<br>31.10.2018 | <b>EPIC<sup>®</sup> SIGNAL M23 KIT F6 12 PINS SOLDER<br/>TERMINATION</b> |                                                                                     |

## Description

- Circular connector for servo cables and encoders
- Low-resistance screen contact
- Optimum EMC protection
- Use of high quality materials for increased reliability
- Complete connector with housing and insulation body, equipped with suitable solder contacts



## Components of the Combination

|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| Article number of the combination | 75009713                                           |
| Housing                           | SIGNAL M23 F6 (44420040)                           |
| Insert                            | 12 (P-Part) Pin with solder termination (73002714) |

## General characteristics

|                                |                              |
|--------------------------------|------------------------------|
| Series                         | SIGNAL M23                   |
| Type                           | F6, Coupling connector       |
| Version                        | Male                         |
| Connection type                | Solder termination           |
| Coding                         | Black (N)                    |
| Pin-arrangement                | 12 (P-Part)                  |
| Contact diameter               | 1 mm                         |
| Termination cross section      | Up to 1 mm <sup>2</sup>      |
| Clamping range                 | 7,0 mm – 13,5 mm             |
| Degree of protection           | IP 68 (10 h / 1 m) (latched) |
| Cycles of mechanical operation | 100                          |
| Temperature range              | -25 °C to +125 °C            |

## Materials and surfaces

|                        |               |
|------------------------|---------------|
| Housing, base material | Zinc die-cast |
| Housing, surface       | Nickel        |
| Sealing                | FPM/FKM       |
| Insert                 | PA            |
| Contact, base material | Brass         |
| Contact, surface       | Gold          |

## Electrical characteristics

|                       |          |
|-----------------------|----------|
| Rated voltage         | 100 V    |
| Rated impulse voltage | 1,5 kV   |
| Rated current         | 7 A      |
| Contact resistance    | < 4 mOhm |
| Verschmutzungsgrad    | 3        |

|                                           |                                       |             |
|-------------------------------------------|---------------------------------------|-------------|
| Creator: STKU3/PDP<br>Released: IVSE1/PDP | Document: DB75009713EN<br>Version: 00 | Page 1 of 3 |
|-------------------------------------------|---------------------------------------|-------------|

|                           |                                                               |                                                                                     |
|---------------------------|---------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 75009713                  | <b>DATA SHEET</b>                                             |  |
| Valid from:<br>31.10.2018 | <b>EPIC® SIGNAL M23 KIT F6 12 PINS SOLDER<br/>TERMINATION</b> |                                                                                     |

## Approvals

VDE-Approval, VDE-REG.-Nr.  
UL File Number

C24  
E249137



## Standards



Safety Standard

IEC 61984


## Technical Drawings

Housing

Anzugsdrehmoment: 7,5 Nm  
tightening torque: 7,5 Nm



Insert




|                                           |                                       |             |
|-------------------------------------------|---------------------------------------|-------------|
| Creator: STKU3/PDP<br>Released: IVSE1/PDP | Document: DB75009713EN<br>Version: 00 | Page 2 of 3 |
|-------------------------------------------|---------------------------------------|-------------|


|                           |                                                               |                                                                                     |
|---------------------------|---------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 75009713                  | <b>DATA SHEET</b>                                             |  |
| Valid from:<br>31.10.2018 | <b>EPIC® SIGNAL M23 KIT F6 12 PINS SOLDER<br/>TERMINATION</b> |                                                                                     |



Good chemical resistance



Industrial machinery and plant engineering



Optimum strain relief



Mechanical resistance



Assembly time



Robust



Integrated SKINTOP® cable gland



Wind energy



Variety of approval certifications

### Info

Robust metal connector with integrated EMC cable gland

### Application range

Plant engineering

Servo drives and Servo assemblies

Measurement and control technology

Apparatus construction

### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

|                                           |                                       |             |
|-------------------------------------------|---------------------------------------|-------------|
| Creator: STKU3/PDP<br>Released: IVSE1/PDP | Document: DB75009713EN<br>Version: 00 | Page 3 of 3 |
|-------------------------------------------|---------------------------------------|-------------|