



**Ecolab Deutschland GmbH
Ecolab Allee 1
D-40789 Monheim am Rhein**

certifies that for

**U.I. Lapp GmbH
Schulze-Delitzsch-Straße 25
70565 Stuttgart**

material resistance tests

were performed with cleaning/disinfecting substances **Topactive 200, Topactive 500, Topactive OKTO, P3-topax 66, P3-topax 990** and demineralized water as a zero reference factor.

The material resistance of the tested

- **SKINTOP® DIX-M SI**
- **SKINTOP® INOX**

to the Ecolab products used in the test can be considered to be positive according to the cleaning procedure mentioned overleaf.

Monheim am Rhein, 19th August 2021

Ecolab Deutschland GmbH

i.A.

Tanja Hackenberger

i. V.

Thomas Tyborski

This certificate is based on:

- documented test procedures (test no.: F&E/P3-E Nr. 40-1) according to material resistance
- defined product descriptions
- test report for the Ecolab certification carried out at U.I. Lapp GmbH, Stuttgart, 04.2021

**Test procedure
Ecolab-test F&E Nr. 40-1**

Test material: see report P090/21

Dipping test:

- Complete immersion in solutions/liquid

Test period:

- 28 days

Temperature:

- room temperature (constant)

Analysis:

- Visual judgement like swelling, brittleness, discoloring
- compared to zero-reference factor (demineralized water)
- Photo documentation
- Function test

Product specifications:

Topactive OKTO

Acid disinfectant based on peracetic acid/hydrogen peroxide for the food and beverage industries

P3-topax 66

Alkaline foam detergent sanitizer with available chlorine for the food and beverage industries

P3-topax 990

Mild-alkaline, chlorine-free sanitizer for the food and beverage industries

Topactive 200

Alkaline, chlorine-free foam cleaner for the food and beverage industry

Topactive 500

Acid foam cleaning substance for the food and beverage industries

Cleaning plan for food and beverage industry*



Rinsing with water 40 – 50°C

Rinsing with low pressure. Rinsing from top to bottom in the direction of the drains. Cleaning of the drains



Foaming from bottom to top

alkaline:	Topactive 200 or P3-topax 66	2 - 5 % daily
acid:	Topactive 500	2 % on demand
temperature:	cold up to 50°C	
contact time:	15 min. recommended	



Rinsing with water 40 – 50°C

Rinsing from top to bottom with low pressure



Foam disinfection

	Topactive OKTO	1 -3%, 10-30 min
alternative	P3-topax 990	1-3 %, 30 min



Rinse with potable water after disinfection!

*short description The final step of a cleaning regime is always a thorough water rinse!