

52005470	DATA SHEET	
Valid from: 03.07.2018	SKINDICHT® SVFK	

The SKINDICHT® SVFK, a flat cable gland made of plastic for universal use. The lateral sealing lips fit around various cable dimensions, so that with only one seal for each PG-size, flat cables of different outside dimensions can be sealed.



Components:

Gland body	Polystyrene
Pressure screw	Polystyrene
Pressure washers	Steel, zinc-plated
Sealing insert	CR

Technical features:



Connecting thread	PG16 up to PG48 acc. to DIN 40430
Protection class	IP54 acc. to EN 60529
Temperature range	-20 °C up to +60 °C
Colour	RAL 7035

Norm references:



Creator: T. Dvoutely /PDP Released: DAMU1/PDP	Document: DB52005470EN Version: 03	Page 1 of 2
--	---------------------------------------	-------------

52005470	DATA SHEET	
Valid from: 03.07.2018	SKINDICHT® SVFK	



PG	SW1 [mm]	Ø A1 [mm]	SW2 [mm]	Ø A2 [mm]	C [mm] max.	D [mm]	Flat cable width [mm] min.-max.	Flat cable thickness [mm] min.-max.	Article No.
PG 16	23	26,0	27	29,5	39,5	11	- - 15	- - 5	52005470
PG 21	30	33,8	33	37,5	47,5	11	10 - 20,5	3 - 8	52005680
PG 29	40	44,8	42	47,5	49,5	12	15 - 27	4 - 11,5	52005690
PG 36	50	56,5	53	60,0	52,5	12	25 - 34	4 - 11,5	52005700
PG 42	55	61,5	60	68,0	58,0	13	30 - 40	5 - 12	52005710
PG 48	60	67,5	65	74,0	59,0	14	35 - 45	5 - 12	52005720

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: T. Dvoutely /PDP Released: DAMU1/PDP	Document: DB52005470EN Version: 03	Page 2 of 2
--	---------------------------------------	-------------