


UNIRAIL S – EN 50264-3-2 600 V – type MM – EN 50200

UNIKA (Italy) – EN 50264-3-2 600 V MM - EN 50200 PH120 - code



TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, fuels, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

According to table 1 of EN 50264-3-2 for cables rated 600V (see IMQ test certificate) with fire resisting time not below 120 min

Item n°	Cross-section [mm ²]	Nominal diameter [mm]	Cable mass [kg/km]
RBA00	2x1,5	8,4	92
RBA01	2x2,5	9,4	122
RBA02	3x1,5	8,9	106
RBA03	3x2,5	10,1	146
RBA04	4x1,5	9,9	137
RBA05	4x2,5	11,1	186
RBA06	2x4	10,4	163

CONSTRUCTION

Type: multicore cable fire resistant

Conductor: tinned copper conductor according to class 5 EN 60228

Tape: mica tape

Insulation: crosslinked compound, type EI109 according to Standard EN 50264-1, colour black with numbers

Tape: non-hygroscopic tape on the assembly

Sheath: crosslinked compound, type EM104 according to Standard EN 50264-1, colour red if not otherwise stated

Marking: UNIKA (Italy) – EN 50264-3-2 600V cross-section MM – EN 50200 PH120 - *traceability code*

Fire safety: Cables are classified in compliance to the highest requirements established by **hazard level HL3** into Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.