

KRD10-2

Proudový chránič, 2P



[Hz]
50

-25÷40

IP
20

2P

2

TH 35

U_i [V]
400

max 25

CE

EAC

UK
CA

KRD10-2/16/30-F

		[V]	In [A]	I _{Δn} [mA]	Typ proudového chrániče	
KRD10-2/16/30-F	45769	230 AC	16	30	F	2
KRD10-2/25/30-F	45770	230 AC	25	30	F	2
KRD10-2/40/30-F	45771	230 AC	40	30	F	2
KRD10-2/25/100-F	45772	230 AC	25	100	F	2
KRD10-2/40/100-F	45773	230 AC	40	100	F	2
KRD10-2/25/300-F	45774	230 AC	25	300	F	2
KRD10-2/40/300-F	45775	230 AC	40	300	F	2

Proudový chránič typu F je modernější verze, navržená pro instalace s elektronikou a jednofázovými měniči. Typ F reaguje na více druhů reziduálního proudu než klasický typ AC nebo A:

AC – střídavý sinusový proud

A – AC + pulzující DC

F – vše výše uvedené + proudy se smíšenými frekvencemi (do cca 1 kHz) a krátkodobé DC složky do 10 mA.

KRD10-2

Proudový chránič, 2P



KRD10-2/16/30-F



KRD10-2/25/30-F



KRD10-2/40/30-F



KRD10-2/25/100-F



KRD10-2/40/100-F



KRD10-2/25/300-F



KRD10-2/40/300-F

