

6.4 ZÁSUVKOVÉ SKŘÍŇE FLATBOX V KRYTÍ IP54 - IP65

6.4 WIRED ENCLOSURES WITH IP65 SOCKETS



1

Obj. č.	Zásuvky	Chránič	Jističe
fb112805	2x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 2x PL7 B16/1
fb112805-6kA	2x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 2x PL6 B16/1



Rozměry	(mm)
Výška	380
Šířka	270
Hloubka	120

Použité pouzdro: 5810

Počet modulů: 10

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



2



3

Obj. č.	Zásuvky	Chránič	Jističe
fb39005	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B16/3 2x PL7 B16/1
fb39005-6kA	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B16/3 2x PL6 B16/1
fb31005	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
fb31005-6kA	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1



Rozměry	(mm)
Výška	380
Šířka	270
Hloubka	120

Použité pouzdro: 5810

Počet modulů: 10

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



4



5

EKO

- Zásuvková skříň je určena jen pro malé proudové odběry
- Zásuvková skříň není vhodná do průmyslu
- 400 V zásuvky mají společný jistič



Obj. č.	Zásuvky	Chránič	Jističe
fb32505	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 3x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
fb32505-6kA	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 3x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1



Rozměry	(mm)
Výška	380
Šířka	270
Hloubka	120

Použité pouzdro: 5813

Počet modulů: 13

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



6



7



8

Obj. č.	Zásuvky	Chránič	Jističe
fb34005	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 4x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B16/3 1x PL7 B16/3 2x PL7 B16/1
fb34005-6kA	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 4x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B16/3 1x PL6 B16/3 2x PL6 B16/1



Rozměry	(mm)
Výška	380
Šířka	270
Hloubka	120

Použité pouzdro: 5813

Počet modulů: 13

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



9



10