

## ZB5CA6939

modrá čtver. zapuř. hlava tlačítka Ø22 s návratem  
"R"



### Hlavní parametry

|                                |                                  |
|--------------------------------|----------------------------------|
| Řada výrobků                   | Harmony XB5                      |
| Typ produktu nebo součásti     | Hlava pro neprosvětlené tlačítko |
| Označení přístroje             | ZB5                              |
| Materiál ohruby                | Dark grey plastic                |
| Průměr pro montáž              | 22 mm                            |
| Typ hlavy                      | Standard                         |
| Prodej v nedělitelném množství | 1                                |
| Tvar hlavice                   | Čtverec                          |
| Typ ovládací hlavice           | S návratem                       |
| Provedení ovládače             | Modrá lícující, bílá R           |

### Doplňk

|                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD celková šířka    | 30 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| CAD celková výřka    | 30 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| CAD celková hloubka  | 28 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Hmotnost přístroje   | 0,019 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Mechanická životnost | 5000000 cykly                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Označení skříně      | XALD 1...5 výřezů<br>XALK 2...5 výřezů                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Označení el. složení | C15 pro 1 kontakty použitím jednoduchých bloky v čelní montáž<br>C15 pro 1 kontakty použitím jednoduchých bloky v čelní montáž<br>C11 pro 3 kontakty použitím jednoduchých bloky v čelní montáž<br>SF1 pro 3 kontakty použitím jednoduchých bloky v čelní montáž<br>C1 for 9 contacts using single blocks in front mounting<br>C2 for 9 contacts using single and double blocks in front mounting<br>SR1 pro 3 kontakty použitím jednoduchých bloky v montáž na desku ve dně skříně |

### Životní prostředí


|                                     |                                                                                                                                                                          |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| stupeň ochrany                      | TH                                                                                                                                                                       |
| teplota okolí pro uskladnění        | -40...70 °C                                                                                                                                                              |
| teplota okolního vzduchu pro provoz | -25...70 °C                                                                                                                                                              |
| kategorie přepětí                   | Třída II podle IEC 60536                                                                                                                                                 |
| stupeň krytí IP                     | IP66 podle IEC 60529                                                                                                                                                     |
| stupeň krytí NEMA                   | NEMA 13<br>NEMA 4X                                                                                                                                                       |
| odolnost proti vysokému tlaku mytí  | 7000000 Pa při 55 °C, vzdálenost: 0,1 m                                                                                                                                  |
| stupeň ochrany IK                   | IK03 podle IEC 50102                                                                                                                                                     |
| standarty                           | EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>JIS C 4520<br>UL 508<br>CSA C22.2 č. 14                                                                        |
| certifikace výrobku                 | BV<br>CSA<br>DNV<br>GL<br>LROS (Lloyds register of shipping)<br>RINA<br>UL listed                                                                                        |
| odolnost proti otřesům              | 30 gn (doba trvání = 18 ms) pro akcelerace polovina sin. vlny podle IEC 60068-2-27<br>50 gn (doba trvání = 11 ms) pro akcelerace polovina sin. vlny podle IEC 60068-2-27 |
| odolnost proti vibracím             | 5 gn (f = 2...500 Hz) podle IEC 60068-2-6                                                                                                                                |

Contractual warranty

Záruční lhůta


18 měsíců

Dimensions



Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)


Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board



- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3) Ø22.5 mm recommended ( $\text{Ø}22.3 \text{ }_0^{+0.4}$ ) / Ø0.89 in. recommended ( $\text{Ø}0.88 \text{ in. }_0^{+0.016}$ )

| Connections                                   | a in mm | a in in. | b in mm | b in in. |
|-----------------------------------------------|---------|----------|---------|----------|
| By screw clamp terminals or plug-in connector | 40      | 1.57     | 30      | 1.18     |
| By Faston connectors                          | 45      | 1.77     | 32      | 1.26     |
| On printed circuit board                      | 30      | 1.18     | 30      | 1.18     |

Detail of Lug Recess




- (1) Diameter on finished panel or support
- (2) For selector switches and Emergency stop buttons, use of an anti-rotation plate type ZB5AZ902 is recommended.
- (3) Ø22.5 mm recommended ( $\text{Ø}22.3 \text{ }_0^{+0.4}$ ) / Ø0.89 in. recommended ( $\text{Ø}0.88 \text{ in. }_0^{+0.016}$ )


Pushbuttons, Switches and Pilot Lights for Printed Circuit Board Connection

Panel Cut-outs (Viewed from Installer's Side)



Dimensions in mm





The cumulative tolerance must not exceed 0.3 mm / 0.012 in.:  $T1 + T2 = 0.3 \text{ mm max.}$

- ┆ Minimum thickness of circuit board: 1.6 mm / 0.06 in.
- ┆ Cut-out diameter: 22.4 mm ± 0.1 / 0.88 in. ± 0.004
- ┆ Orientation of body/fixing collar ZB5AZ009: ± 2°30' (excluding cut-outs marked **a** and **b**).
- ┆ Tightening torque of screws ZBZ006: 0.6 N.m (5.3 lbf.in) max.
- ┆ Allow for one ZB5AZ079 fixing collar/pillar and its fixing screws:
  - ┆ every 90 mm / 3.54 in. horizontally (X), and 120 mm / 4.72 in. vertically (Y).
  - ┆ with each selector switch head (ZB5AD•, ZB5AJ•, ZB5AG•).

Technical drawing of a valve assembly (ZBE 70/ZBV B.7) showing dimensions and labels. The drawing includes a side view of the valve with a blue highlight on the handle. Dimensions are indicated with arrows and values: 49,75 ± 0,3, 1,98 ± 0,012, 55,4 max, and 2,18 max. Labels include (1), (2), (3), (4), ZB5 AZ079, ZBE 70/ZBV B.7, ZBZ 01, and ZBZ 008. A scale bar at the top left indicates mm and 1/8".

- (1) Head ZB5AD•
- (2) Panel
- (2) Nut
- (4) Printed circuit board


- | **1** 2 elongated holes for ZBZ006 screw access
- | **2** 1 hole  $\varnothing$  2.4 mm  $\pm$  0.05 / 0.09 in.  $\pm$  0.002 for centring adapter ZBZ01\*
- | **3** 8  $\times$   $\varnothing$  1.2 mm / 0.05 in. holes
- | **4** 1 hole  $\varnothing$  2.9 mm  $\pm$  0.05 / 0.11 in.  $\pm$  0.002, for aligning the printed circuit board (with cut-out marked **a**)

┆ 5 1 elongated hole for aligning the printed circuit board (with cut-out marked **b**)

┆ 6 4 holes Ø 2.4 mm / 0.09 in. for clipping in adapter ZBZ01•

Dimensions An + 18.1 relate to the Ø 2.4 mm ± 0.05 / 0.09 in. ± 0.002 holes for centring adapter ZBZ01•.

## Electrical Composition Corresponding to Code C1



## Electrical Composition Corresponding to Code C2




## Electrical Composition Corresponding to Codes C9, C11, SF1 and SR1




## Electrical Composition Corresponding to Code C15


1 N/O



1 N/C



1 N/O + N/C or 1 N/O + N/O or 1 N/C + N/C



## Legend

Single contact



Double contact



Light block



Possible location

