

6.2 ZÁSUVKOVÉ SKŘÍŇE A STAVENIŠTNÍ ROZVÁDĚČE V KRYTÍ IP54 - IP65

6.2 WIRED ENCLOSURES WITH IP65 SOCKETS



1

Obj. č.	Zásuvky	Chránič	Jističe
v594	1x 400 V / 32 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 2x PL7 B16/1
v594-6kA	1x 400 V / 32 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 2x PL6 B16/1



Rozměry (mm)	
Výška	330
Šířka	330
Hloubka	155

Použité pouzdro: 3974

Počet modulů: 16

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



2



3

Obj. č.	Zásuvky	Chránič	Jističe
v210	1x 400 V / 32 A / 5p 3x 230 V / 16 A / 3p	Pouze vydrátovaná	
v213	1x 400 V / 32 A / 5p 3x 230 V / 16 A / 3p	-	1x PL7 B32/3 2x PL7 B16/1
v213-6kA	1x 400 V / 32 A / 5p 3x 230 V / 16 A / 3p	-	1x PL6 B32/3 2x PL6 B16/1
v214	1x 400 V / 32 A / 5p 3x 230 V / 16 A / 3p	-	1x PL7 B32/3 3x PL7 B16/1
v214-6kA	1x 400 V / 32 A / 5p 3x 230 V / 16 A / 3p	-	1x PL6 B32/3 3x PL6 B16/1
v215	1x 400 V / 32 A / 5p 3x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 2x PL7 B16/1
v215-6kA	1x 400 V / 32 A / 5p 3x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 2x PL6 B16/1



Rozměry (mm)	
Výška	330
Šířka	215
Hloubka	155

Použité pouzdro: 3958

Počet modulů: 9

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



4



5

Obj. č.	Zásuvky	Chránič	Jističe
v572	1x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	Pouze vydrátovaná	
v575	1x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	-	1x PL7 B32/3 2x PL7 B16/1
v575-6kA	1x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	-	1x PL6 B32/3 2x PL6 B16/1
v577	1x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	-	1x PL7 B32/3 4x PL7 B16/1
v577-6kA	1x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	-	1x PL6 B32/3 4x PL6 B16/1
v580	1x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 2x PL7 B16/1
v580-6kA	1x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 2x PL6 B16/1



Rozměry (mm)	
Výška	330
Šířka	215
Hloubka	155

Použité pouzdro: 3958

Počet modulů: 9

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



6



7



8

Obj. č.	Zásuvky	Chránič	Jističe
v295	1x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	Pouze vydrátovaná	
v297	1x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	-	1x PL7 B32/3 2x PL7 B16/1
v297-6kA	1x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	-	1x PL6 B32/3 2x PL6 B16/1



Rozměry (mm)	
Výška	490
Šířka	125
Hloubka	107

Použité pouzdro: 3950

Počet modulů: 6

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



9



10

TOP