

6.2 ZÁSUVKOVÉ SKŘÍŇE A STAVENIŠTNÍ ROZVÁDĚČE V KRYTÍ IP54 - IP65

6.2 WIRED ENCLOSURES WITH IP65 SOCKETS



1

Obj. č.	Zásuvky	Chránič	Jističe
v4256	2x 400 V / 32 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 2x PL7 B16/1
v4256-6kA	2x 400 V / 32 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 2x PL6 B16/1



Rozměry	(mm)
Výška	330
Šířka	215
Hloubka	155

Použité pouzdro: 3958

Počet modulů: 9

Stupeň krytí: IP65

Normy: EN 62208, IEC 61439-3



2



3

Obj. č.	Zásuvky	Chránič	Jističe
v266	2x 400 V / 32 A / 5p 2x 230 V / 16 A / 3p	Pouze vydrátovaná	
v268	2x 400 V / 32 A / 5p 2x 230 V / 16 A / 3p	-	1x PL7 B32/3 2x PL7 B16/1
v268-6kA	2x 400 V / 32 A / 5p 2x 230 V / 16 A / 3p	-	1x PL6 B32/3 2x PL6 B16/1



Rozměry	(mm)
Výška	490
Šířka	125
Hloubka	107

Použité pouzdro: 3950

Počet modulů: 6

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



4



5

Obj. č.	Zásuvky	Chránič	Jističe
v600	2x 400 V / 32 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	2x PL7 B32/3 2x PL7 B16/1
v600-6kA	2x 400 V / 32 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	2x PL6 B32/3 2x PL6 B16/1



Rozměry	(mm)
Výška	330
Šířka	330
Hloubka	155

Použité pouzdro: 3974

Počet modulů: 16

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



6



7



8



9



10

Obj. č.	Zásuvky	Chránič	Jističe
v348	2x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	1x PF7 40/4/003	2x PL7 B32/3 2x PL7 B16/1
v348-6kA	2x 400 V / 32 A / 5p 4x 230 V / 16 A / 3p	1x PF6 40/4/003	2x PL6 B32/3 2x PL6 B16/1



Rozměry	(mm)
Výška	398
Šířka	266
Hloubka	153

Použité pouzdro: 3959

Počet modulů: 12

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3

TOP