

6.2 ZÁSUVKOVÉ SKŘÍŇE A STAVENIŠTNÍ ROZVÁDĚČE V KRYTÍ IP54 - IP65

6.2 WIRED ENCLOSURES WITH IP65 SOCKETS



1

Obj. č.	Zásuvky	Chránič	Jističe
v4415	2x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	2x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v4415-6kA	2x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	2x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1
v441	2x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v441-6kA	2x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1



Rozměry (mm)	
Výška	500
Šířka	330
Hloubka	155

Použité pouzdro: 3952
Počet modulů: 16
Stupeň krytí: IP54
Normy: EN 62208, IEC 61439-3



2



3

Obj. č.	Zásuvky	Chránič	Jističe
v630	2x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 4x 230 V / 16 A / 3p	-	2x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v630-6kA	2x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 4x 230 V / 16 A / 3p	-	2x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1
v632	2x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 4x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v632-6kA	2x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 4x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1



Rozměry (mm)	
Výška	500
Šířka	330
Hloubka	155

Použité pouzdro: 3952
Počet modulů: 16
Stupeň krytí: IP54
Normy: EN 62208, IEC 61439-3



4



5

Obj. č.	Zásuvky	Chránič	Jističe
v837	2x 400 V / 32 A / 5p 2x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	Pouze vydrátovaná	
v839	2x 400 V / 32 A / 5p 2x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	2x PL7 B32/3 2x PL7 B16/3 1x PL7 B16/1
v839-6kA	2x 400 V / 32 A / 5p 2x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	2x PL6 B32/3 2x PL6 B16/3 1x PL6 B16/1
v840	2x 400 V / 32 A / 5p 2x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v840-6kA	2x 400 V / 32 A / 5p 2x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1
TOP v845	2x 400 V / 32 A / 5p 2x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v845-6kA	2x 400 V / 32 A / 5p 2x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1
v847	2x 400 V / 32 A / 5p 2x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 63/4/003	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v847-6kA	2x 400 V / 32 A / 5p 2x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 63/4/003	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1



Rozměry (mm)	
Výška	500
Šířka	330
Hloubka	155

Použité pouzdro: 3952
Počet modulů: 16
Stupeň krytí: IP54
Normy: EN 62208, IEC 61439-3



6



7



8



9



10