

## 6.2 ZÁSUVKOVÉ SKŘÍŇE A STAVENIŠTNÍ ROZVÁDĚČE V KRYTÍ IP54 - IP65

### 6.2 WIRED ENCLOSURES WITH IP65 SOCKETS



1

| Obj. č.         | Zásuvky                                                            | Chránič         | Jističe                                      |
|-----------------|--------------------------------------------------------------------|-----------------|----------------------------------------------|
| <b>v965</b>     | 1x 400 V / 32 A / 5p<br>1x 24 V / 6 A / 2p<br>1x 230 V / 16 A / 3p | 1x PF7 40/4/003 | 1x PL7 B32/3<br>1x PL7 B 6/2<br>1x PL7 B16/1 |
| <b>v965-6kA</b> | 1x 400 V / 32 A / 5p<br>1x 24 V / 6 A / 2p<br>1x 230 V / 16 A / 3p | 1x PF6 40/4/003 | 1x PL6 B32/3<br>1x PL6 B 6/2<br>1x PL6 B16/1 |



| Rozměry (mm) |     |
|--------------|-----|
| Výška        | 500 |
| Šířka        | 330 |
| Hloubka      | 155 |

Použité pouzdro: 3952

Počet modulů: 16

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



2



3

| Obj. č.         | Zásuvky                                                            | Chránič         | Jističe                                      |
|-----------------|--------------------------------------------------------------------|-----------------|----------------------------------------------|
| <b>v925</b>     | 1x 400 V / 32 A / 5p<br>1x 24 V / 6 A / 2p<br>2x 230 V / 16 A / 3p | -               | 1x PL7 B32/3<br>1x PL7 B 6/2<br>2x PL7 B16/1 |
| <b>v925-6kA</b> | 1x 400 V / 32 A / 5p<br>1x 24 V / 6 A / 2p<br>2x 230 V / 16 A / 3p | -               | 1x PL6 B32/3<br>1x PL6 B 6/2<br>2x PL6 B16/1 |
| <b>v930</b>     | 1x 400 V / 32 A / 5p<br>1x 24 V / 6 A / 2p<br>2x 230 V / 16 A / 3p | 1x PF7 40/4/003 | 1x PL7 B32/3<br>1x PL7 B 6/2<br>2x PL7 B16/1 |
| <b>v930-6kA</b> | 1x 400 V / 32 A / 5p<br>1x 24 V / 6 A / 2p<br>2x 230 V / 16 A / 3p | 1x PF6 40/4/003 | 1x PL6 B32/3<br>1x PL6 B 6/2<br>2x PL6 B16/1 |



| Rozměry (mm) |     |
|--------------|-----|
| Výška        | 500 |
| Šířka        | 330 |
| Hloubka      | 155 |

Použité pouzdro: 3952

Počet modulů: 16

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



4



5

| Obj. č.         | Zásuvky                                                            | Chránič         | Jističe                                      |
|-----------------|--------------------------------------------------------------------|-----------------|----------------------------------------------|
| <b>v898</b>     | 2x 400 V / 32 A / 5p<br>1x 24 V / 6 A / 2p<br>1x 230 V / 16 A / 3p | -               | 2x PL7 B32/3<br>1x PL7 B 6/2<br>1x PL7 B16/1 |
| <b>v898-6kA</b> | 2x 400 V / 32 A / 5p<br>1x 24 V / 6 A / 2p<br>1x 230 V / 16 A / 3p | -               | 2x PL6 B32/3<br>1x PL6 B 6/2<br>1x PL6 B16/1 |
| <b>v901</b>     | 2x 400 V / 32 A / 5p<br>1x 24 V / 6 A / 2p<br>1x 230 V / 16 A / 3p | 1x PF7 63/4/003 | 2x PL7 B32/3<br>1x PL7 B 6/2<br>1x PL7 B16/1 |
| <b>v901-6kA</b> | 2x 400 V / 32 A / 5p<br>1x 24 V / 6 A / 2p<br>1x 230 V / 16 A / 3p | 1x PF6 63/4/003 | 2x PL6 B32/3<br>1x PL6 B 6/2<br>1x PL6 B16/1 |



| Rozměry (mm) |     |
|--------------|-----|
| Výška        | 500 |
| Šířka        | 330 |
| Hloubka      | 155 |

Použité pouzdro: 3952

Počet modulů: 16

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



6



7

| Obj. č.         | Zásuvky                                                                                    | Chránič         | Jističe                                                      |
|-----------------|--------------------------------------------------------------------------------------------|-----------------|--------------------------------------------------------------|
| <b>v945</b>     | 1x 400 V / 32 A / 5p<br>1x 400 V / 16 A / 5p<br>1x 24 V / 6 A / 2p<br>1x 230 V / 16 A / 3p | -               | 1x PL7 B32/3<br>1x PL7 B16/3<br>1x PL7 B 6/2<br>1x PL7 B16/1 |
| <b>v945-6kA</b> | 1x 400 V / 32 A / 5p<br>1x 400 V / 16 A / 5p<br>1x 24 V / 6 A / 2p<br>1x 230 V / 16 A / 3p | -               | 1x PL6 B32/3<br>1x PL6 B16/3<br>1x PL6 B 6/2<br>1x PL6 B16/1 |
| <b>v948</b>     | 1x 400 V / 32 A / 5p<br>1x 400 V / 16 A / 5p<br>1x 24 V / 6 A / 2p<br>1x 230 V / 16 A / 3p | 1x PF7 40/4/003 | 1x PL7 B32/3<br>1x PL7 B16/3<br>1x PL7 B 6/2<br>1x PL7 B16/1 |
| <b>v948-6kA</b> | 1x 400 V / 32 A / 5p<br>1x 400 V / 16 A / 5p<br>1x 24 V / 6 A / 2p<br>1x 230 V / 16 A / 3p | 1x PF6 40/4/003 | 1x PL6 B32/3<br>1x PL6 B16/3<br>1x PL6 B 6/2<br>1x PL6 B16/1 |



| Rozměry (mm) |     |
|--------------|-----|
| Výška        | 500 |
| Šířka        | 330 |
| Hloubka      | 155 |

Použité pouzdro: 3952

Počet modulů: 16

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



8



9



10