

ALIN LED 11W 590mm PT

Lineární LED svítidlo



[V] 220-240 AC	[Hz] 50	[h] ≥30000	[h] 50000	ellipse ≤ 60° MacAdam	Ra ≥80	SMD
IP 20	5+25	0,5m	CE	EAC		



AL 11W-830-MAT-B-PT

		[W]	Tc [K]	TYPE	[°]		[lm]	[mm]
AL 11W-830-MAT-B-PT	29650	11	3000	matná	X85/Y95	černá	1100	590
AL 11W-830-MAT-SR-PT	29651	11	3000	matná	X85/Y95	stříbrná	1100	590
AL 11W-830-MAT-W-PT	29652	11	3000	matná	X85/Y95	bílá	1100	590
AL 11W-830-MPR-B-PT	29653	11	3000	mikroprizmatický	X75/Y90	černá	1000	590
AL 11W-830-MPR-SR-PT	29654	11	3000	mikroprizmatický	X75/Y90	stříbrná	1000	590
AL 11W-830-MPR-W-PT	29655	11	3000	mikroprizmatický	X75/Y90	bílá	1000	590
AL 11W-840-MAT-B-PT	29656	11	4000	matná	X85/Y95	černá	1150	590
AL 11W-840-MAT-SR-PT	29657	11	4000	matná	X85/Y95	stříbrná	1150	590
AL 11W-840-MAT-W-PT	29658	11	4000	matná	X85/Y95	bílá	1150	590
AL 11W-840-MPR-B-PT	29659	11	4000	mikroprizmatický	X75/Y90	černá	1050	590
AL 11W-840-MPR-SR-PT	29660	11	4000	mikroprizmatický	X75/Y90	stříbrná	1050	590
AL 11W-840-MPR-W-PT	29661	11	4000	mikroprizmatický	X75/Y90	bílá	1050	590

- Materiál korpusu: ocel
- Materiál difuzoru: plast

ALIN LED 11W 590mm PT

Lineární LED svítidlo



AL 11W-830-MAT-B-PT



AL 11W-830-MAT-SR-PT



AL 11W-830-MAT-W-PT



AL 11W-830-MPR-B-PT



AL 11W-830-MPR-SR-PT



AL 11W-830-MPR-W-PT



AL 11W-840-MAT-B-PT



AL 11W-840-MAT-SR-PT



AL 11W-840-MAT-W-PT




AL 11W-840-MPR-B-PT




AL 11W-840-MPR-SR-PT




AL 11W-840-MPR-W-PT




AL 11W-830-MAT-B-PT



AL 11W-830-MAT-SR-PT




AL 11W-830-MAT-W-PT




AL 11W-830-MPR-B-PT

ALIN LED 11W 590mm PT


Lineární LED svítidlo




AL 11W-830-MPR-SR-PT




AL 11W-830-MPR-W-PT




AL 11W-840-MAT-B-PT




AL 11W-840-MAT-SR-PT




AL 11W-840-MAT-W-PT



AL 11W-840-MPR-B-PT



AL 11W-840-MPR-SR-PT



AL 11W-840-MPR-W-PT