

circuit breaker 3VA1 IEC frame 100 breaking capacity class N  
Icu=25kA @ 415V 3-pole, line protection TM210, FTFM, In=32A  
overload protection Ir=32A fixed short-circuit protection Ii=10 x In  
clamp connection

| Model                                          |                             |
|------------------------------------------------|-----------------------------|
| product brand name                             | SENTRON                     |
| product designation                            | Molded case circuit breaker |
| Product version                                | Line protection             |
| design of the overcurrent release              | TM210                       |
| protection function of the overcurrent release | LI                          |
| number of poles                                | 3                           |

| General technical data                                                                         |         |
|------------------------------------------------------------------------------------------------|---------|
| Tension assignée d'isolement Ui                                                                | 800 V   |
| Max. rated operational voltage Ue with AC 50/60Hz                                              | 690 V   |
| Max. rated operational voltage Ue with DC                                                      | 500 V   |
| power loss [W] / maximum                                                                       | 10.6 W  |
| Active power loss / for rated value of the current / at AC / in hot operating state / per pole | 3.53 W  |
| mechanical service life (switching cycles) / typical                                           | 15 000  |
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz                      | 8 000   |
| Electrical endurance (switching cycles) / at AC-1 / at 690 V 50/60 Hz                          | 8 000   |
| Neutral conductors / upgradeable/retrofitable                                                  | No      |
| ground fault monitoring version                                                                | Without |
| product function                                                                               |         |
| • communication function                                                                       | No      |
| • other measurement function                                                                   | No      |
| net weight                                                                                     | 0.9 kg  |

| Current                                          |         |
|--------------------------------------------------|---------|
| Max. rated operational current of the frame size | 100 A   |
| Courant permanent assigné Iu                     | 32 A    |
| operating current                                |         |
| • at 40 °C                                       | 32 A    |
| • at 45 °C                                       | 32 A    |
| • at 50 °C                                       | 32 A    |
| • at 55 °C                                       | 31.04 A |
| • at 60 °C                                       | 31 A    |

- at 65 °C
- at 70 °C

30 A  
30 A

#### Switching capacity according to IEC 60947

|                                                           |                                                                                                                                                                |
|-----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| switching capacity class of the circuit breaker           | N                                                                                                                                                              |
| maximum short-circuit current breaking capacity (Icu)     |                                                                                                                                                                |
| • at 240 V                                                | 36 kA                                                                                                                                                          |
| • at 415 V                                                | 25 kA                                                                                                                                                          |
| • at 440 V                                                | 16 kA                                                                                                                                                          |
| • at 500 V                                                | 5 kA                                                                                                                                                           |
| • at 690 V                                                | 5 kA                                                                                                                                                           |
| operational short-circuit current breaking capacity (Ics) |                                                                                                                                                                |
| • at 240 V                                                | 36 kA                                                                                                                                                          |
| • at 415 V                                                | 25 kA                                                                                                                                                          |
| • at 440 V                                                | 16 kA                                                                                                                                                          |
| • at 500 V                                                | 5 kA                                                                                                                                                           |
| • at 690 V                                                | 5 kA                                                                                                                                                           |
| short-circuit current making capacity (Icm)               |                                                                                                                                                                |
| • at 240 V                                                | 76 kA                                                                                                                                                          |
| • at 415 V                                                | 53 kA                                                                                                                                                          |
| • at 440 V                                                | 32 kA                                                                                                                                                          |
| • at 500 V                                                | 7.5 kA                                                                                                                                                         |
| • at 690 V                                                | 7.5 kA                                                                                                                                                         |
| design of short-circuit protection                        | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |

#### Adjustable parameters

|                                                                         |       |
|-------------------------------------------------------------------------|-------|
| Adjustable response value current / I <sub>g</sub> min.                 | 32 A  |
| Adjustable response value current / I <sub>g</sub> min.                 | 32 A  |
| Short-term delayed / tripping switchable / I <sub>2t</sub> =ON/OFF      | No    |
| Adjustable response value current / I <sub>i</sub> min.                 | 320 A |
| Adjustable response value current / I <sub>i</sub> max.                 | 320 A |
| Ground fault protection / tripping switchable / I <sub>2t</sub> =ON/OFF | No    |

#### Mechanical Design

|             |         |
|-------------|---------|
| height [in] | 5.1 in  |
| Height      | 130 mm  |
| width [in]  | 3 in    |
| Width       | 76.2 mm |
| depth [in]  | 2.8 in  |
| depth       | 70 mm   |

| Connections                                                                     |                    |
|---------------------------------------------------------------------------------|--------------------|
| arrangement of electrical connectors / for main current circuit                 | Front terminal     |
| Type of connectable conductor cross-section, round conductor terminal, stranded | 1 x (1.5 - 70 mm²) |

| Auxiliary circuit                              |   |
|------------------------------------------------|---|
| number of CO contacts / for auxiliary contacts | 0 |

| Accessories                                |    |
|--------------------------------------------|----|
| product extension / optional / motor drive | No |

| Environmental conditions           |        |
|------------------------------------|--------|
| protection class IP / on the front | IP40   |
| ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

| Certificates                            |   |
|-----------------------------------------|---|
| reference code / acc. to DIN EN 81346-2 | Q |

| General Product Approval                                                                   | EMC                                                                                          | Declaration of Conformity                                                                         |
|--------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| <br>CCC | <br>EAC   | <br>EG-Konf. |
| <br>VDE | <br>RCM |                                                                                                   |

[Miscellaneous](#)

| Test Certificates                                  | Shipping Approval                                                                                       |
|----------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| <a href="#">Type Test Certificates/Test Report</a> | <br>ABS              |
| <a href="#">Miscellaneous</a>                      | <br>BUREAU VERITAS |
| <a href="#">Special Test Certificate</a>           | <br>LRS            |

| Shipping Approval                                                                           | other                                              |
|---------------------------------------------------------------------------------------------|----------------------------------------------------|
| <br>RMRS | <a href="#">CCS / China Classification Society</a> |
|                                                                                             | <a href="#">Manufacturer Declaration</a>           |
|                                                                                             | <a href="#">Miscellaneous</a>                      |

| Further information                                                                                                                                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Information- and Downloadcenter (Catalogs, Brochures,...)</b><br><a href="http://www.siemens.com/lowvoltage/catalogs">http://www.siemens.com/lowvoltage/catalogs</a> |

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA1032-3ED36-0AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3VA1032-3ED36-0AA0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA1032-3ED36-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA1032-3ED36-0AA0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

**last modified:**

10/29/2020