

circuit breaker 3VA1 IEC frame 1000 breaking capacity class C  
Icu=110kA @ 415V 4-pole, line protection TM240, ATAM, In=800A  
overload protection Ir=560A...800A short-circuit protection Ii=5...10 x  
In N conductor protection 100% nut keeper kit



| Model                                          |                             |
|------------------------------------------------|-----------------------------|
| product brand name                             | SETRON                      |
| product designation                            | Molded case circuit breaker |
| Product version                                | Line protection             |
| design of the overcurrent release              | TM240                       |
| protection function of the overcurrent release | LI                          |
| number of poles                                | 4                           |

| General technical data                                                                         |         |
|------------------------------------------------------------------------------------------------|---------|
| Tension assignée d'isolement Ui                                                                | 800 V   |
| Max. rated operational voltage Ue with AC 50/60Hz                                              | 690 V   |
| Max. rated operational voltage Ue with DC                                                      | 1 000 V |
| power loss [W] / maximum                                                                       | 240 W   |
| Active power loss / for rated value of the current / at AC / in hot operating state / per pole | 80 W    |
| mechanical service life (switching cycles) / typical                                           | 10 000  |
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz                      | 4 600   |
| Electrical endurance (switching cycles) / at AC-1 / at 690 V 50/60 Hz                          | 3 200   |

|                                               |         |
|-----------------------------------------------|---------|
| Neutral conductors / upgradeable/retrofitable | No      |
| ground fault monitoring version               | Without |
| product function                              |         |
| • communication function                      | No      |
| • other measurement function                  | No      |

#### Current

|                                                  |         |
|--------------------------------------------------|---------|
| Max. rated operational current of the frame size | 1 000 A |
| Courant permanent assigné lu                     | 800 A   |
| operating current                                |         |
| • at 40 °C                                       | 800 A   |
| • at 45 °C                                       | 800 A   |
| • at 50 °C                                       | 800 A   |
| • at 55 °C                                       | 780 A   |
| • at 60 °C                                       | 761 A   |
| • at 65 °C                                       | 741 A   |
| • at 70 °C                                       | 722 A   |

#### Switching capacity according to IEC 60947

|                                                           |                                                                                                                                                                |
|-----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| switching capacity class of the circuit breaker           | C                                                                                                                                                              |
| maximum short-circuit current breaking capacity (Icu)     |                                                                                                                                                                |
| • at 240 V                                                | 200 kA                                                                                                                                                         |
| • at 415 V                                                | 110 kA                                                                                                                                                         |
| • at 440 V                                                | 110 kA                                                                                                                                                         |
| • at 500 V                                                | 70 kA                                                                                                                                                          |
| • at 690 V                                                | 35 kA                                                                                                                                                          |
| operational short-circuit current breaking capacity (Ics) |                                                                                                                                                                |
| • at 240 V                                                | 150 kA                                                                                                                                                         |
| • at 415 V                                                | 85 kA                                                                                                                                                          |
| • at 440 V                                                | 70 kA                                                                                                                                                          |
| • at 500 V                                                | 65 kA                                                                                                                                                          |
| • at 690 V                                                | 19 kA                                                                                                                                                          |
| short-circuit current making capacity (Icm)               |                                                                                                                                                                |
| • at 240 V                                                | 440 kA                                                                                                                                                         |
| • at 415 V                                                | 242 kA                                                                                                                                                         |
| • at 440 V                                                | 242 kA                                                                                                                                                         |
| • at 500 V                                                | 147 kA                                                                                                                                                         |
| • at 690 V                                                | 74 kA                                                                                                                                                          |
| design of short-circuit protection                        | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |

#### Adjustable parameters

|                                                                         |         |
|-------------------------------------------------------------------------|---------|
| Adjustable response value current / I <sub>g</sub> min.                 | 560 A   |
| Adjustable response value current / I <sub>g</sub> min.                 | 800 A   |
| Adjustable response value current / I <sub>i</sub> min.                 | 4 000 A |
| Adjustable response value current / I <sub>i</sub> max.                 | 8 000 A |
| design of the N-conductor protection                                    | 100%    |
| Ground fault protection / tripping switchable / I <sub>2</sub> t=ON/OFF | No      |

### Mechanical Design

|             |         |
|-------------|---------|
| height [in] | 12.6 in |
| Height      | 320 mm  |
| width [in]  | 11 in   |
| Width       | 280 mm  |
| depth [in]  | 4.7 in  |
| depth       | 120 mm  |

### Connections

|                                                                                         |                |
|-----------------------------------------------------------------------------------------|----------------|
| arrangement of electrical connectors / for main current circuit                         | Front terminal |
| Type of connectable conductor cross-section, connection screw, width x thickness , min. | 20 x 4 mm      |

### Auxiliary circuit

|                                                |   |
|------------------------------------------------|---|
| number of CO contacts / for auxiliary contacts | 0 |
|------------------------------------------------|---|

### Accessories

|                                            |     |
|--------------------------------------------|-----|
| product extension / optional / motor drive | Yes |
|--------------------------------------------|-----|

### Environmental conditions

|                                    |        |
|------------------------------------|--------|
| protection class IP / on the front | IP40   |
| ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

### Certificates

|                                         |   |
|-----------------------------------------|---|
| reference code / acc. to DIN EN 81346-2 | Q |
|-----------------------------------------|---|

| General Product Approval                                                                 | EMC                                                                                      | Declaration of Conformity                                                                | Test Certificates                                                                               |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <br>VDE | <br>EAC | <br>RCM | <br>EG-Konf. |

[Miscellaneous](#)

[Miscellaneous](#)

| Test Certificates                                                                                                                              | Shipping Approval                        | other                         |
|------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|-------------------------------|
| <a href="#">Type Test Certificates/Test Report</a><br><br>LRS | <a href="#">Manufacturer Declaration</a> | <a href="#">Miscellaneous</a> |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA1580-7GF42-0AA0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA1580-7GF42-0AA0>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)





[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA1580-7GF42-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA1580-7GF42-0AA0)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>





last modified:

10/30/2020