

circuit breaker 3VA2 IEC frame 1000 breaking capacity class C  
Icu=110kA @ 415V 3-pole, line protection ETU320, LI, In=1000A  
overload protection Ir=400A...1000A short-circuit protection  
Ii=1.5...10 x In nut keeper kit



| Model                                          |                             |
|------------------------------------------------|-----------------------------|
| product brand name                             | SETRON                      |
| product designation                            | Molded case circuit breaker |
| Product version                                | Line protection             |
| design of the overcurrent release              | ETU320                      |
| protection function of the overcurrent release | LI                          |
| number of poles                                | 3                           |

| General technical data                                                                         |        |
|------------------------------------------------------------------------------------------------|--------|
| Tension assignée d'isolement Ui                                                                | 800 V  |
| Max. rated operational voltage Ue with AC 50/60Hz                                              | 690 V  |
| power loss [W] / maximum                                                                       | 330 W  |
| Active power loss / for rated value of the current / at AC / in hot operating state / per pole | 110 W  |
| mechanical service life (switching cycles) / typical                                           | 10 000 |
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz                      | 4 900  |
| Electrical endurance (switching cycles) / at AC-1 / at 690 V 50/60 Hz                          | 3 400  |
| Neutral conductors / upgradeable/retrofitable                                                  | No     |

|                                 |         |
|---------------------------------|---------|
| ground fault monitoring version | Without |
| product function                |         |
| • communication function        | No      |
| • other measurement function    | No      |

### Current

|                                                  |         |
|--------------------------------------------------|---------|
| Max. rated operational current of the frame size | 1 000 A |
| Courant permanent assigné Iu                     | 1 000 A |
| operating current                                |         |
| • at 40 °C                                       | 1 000 A |
| • at 45 °C                                       | 1 000 A |
| • at 50 °C                                       | 1 000 A |
| • at 55 °C                                       | 1 000 A |
| • at 60 °C                                       | 955 A   |
| • at 65 °C                                       | 885 A   |
| • at 70 °C                                       | 815 A   |

### Switching capacity according to IEC 60947

|                                                           |        |
|-----------------------------------------------------------|--------|
| switching capacity class of the circuit breaker           | C      |
| maximum short-circuit current breaking capacity (Icu)     |        |
| • at 240 V                                                | 200 kA |
| • at 415 V                                                | 110 kA |
| • at 440 V                                                | 110 kA |
| • at 500 V                                                | 85 kA  |
| • at 690 V                                                | 35 kA  |
| operational short-circuit current breaking capacity (Ics) |        |
| • at 240 V                                                | 150 kA |
| • at 415 V                                                | 85 kA  |
| • at 440 V                                                | 70 kA  |
| • at 500 V                                                | 65 kA  |
| • at 690 V                                                | 19 kA  |
| short-circuit current making capacity (Icm)               |        |
| • at 240 V                                                | 440 kA |
| • at 415 V                                                | 242 kA |
| • at 440 V                                                | 242 kA |
| • at 500 V                                                | 187 kA |
| • at 690 V                                                | 74 kA  |

### Adjustable parameters

|                                                         |         |
|---------------------------------------------------------|---------|
| Adjustable response value current / I <sub>g</sub> min. | 400 A   |
| Adjustable response value current / I <sub>g</sub> min. | 1 000 A |
| Adjustable response value current / I <sub>g</sub> min. | 0.5     |
| Adjustable response value current / I <sub>g</sub> min. | 17      |

|                                                            |          |
|------------------------------------------------------------|----------|
| Adjustable response value current / li min.                | 1 500 A  |
| Adjustable response value current / li max.                | 10 000 A |
| Ground fault protection / tripping switchable / I2t=ON/OFF | No       |

### Mechanical Design

|             |         |
|-------------|---------|
| height [in] | 12.6 in |
| Height      | 320 mm  |
| width [in]  | 8.3 in  |
| Width       | 210 mm  |
| depth [in]  | 4.7 in  |
| depth       | 120 mm  |

### Connections

|                                                                                         |                              |
|-----------------------------------------------------------------------------------------|------------------------------|
| arrangement of electrical connectors / for main current circuit                         | Front terminal               |
| type of electrical connection / for main current circuit                                | on both sides nut keeper kit |
| Type of connectable conductor cross-section, connection screw, width x thickness , min. | 20 x 4 mm                    |

### Auxiliary circuit

|                                                |   |
|------------------------------------------------|---|
| number of CO contacts / for auxiliary contacts | 0 |
|------------------------------------------------|---|

### Environmental conditions

|                                    |        |
|------------------------------------|--------|
| protection class IP / on the front | IP40   |
| ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

### Certificates

|                                         |   |
|-----------------------------------------|---|
| reference code / acc. to DIN EN 81346-2 | Q |
|-----------------------------------------|---|

| General Product Approval | EMC | Declaration of Conformity |
|--------------------------|-----|---------------------------|
|--------------------------|-----|---------------------------|



CCC



VDE

[Miscellaneous](#)



RCM



EG-Konf.

| Test Certificates | Shipping Approval | other |
|-------------------|-------------------|-------|
|-------------------|-------------------|-------|

[Miscellaneous](#)



LRS

[CCS / China Classification Society](#)

[Manufacturer Declaration](#)

[Miscellaneous](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2510-7HL32-0AA0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2510-7HL32-0AA0>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)





[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2510-7HL32-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2510-7HL32-0AA0)


### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>





last modified:

10/30/2020