

circuit breaker 3VA2 IEC frame 160 breaking capacity class M  
Icu=55kA @ 415V 4-pole, line protection ETU550, LSI, In=25A  
overload protection Ir=10A...25A short-circuit protection Isd=0.6..10x  
In, li=1.5..12x In N conductor protection adjustable (OFF, up to  
160%) clamp connection

| Model                                          |                             |
|------------------------------------------------|-----------------------------|
| product brand name                             | SENTRON                     |
| product designation                            | Molded case circuit breaker |
| Product version                                | Line protection             |
| design of the overcurrent release              | ETU550                      |
| protection function of the overcurrent release | LSI                         |
| number of poles                                | 4                           |

| General technical data                                                                         |         |
|------------------------------------------------------------------------------------------------|---------|
| Tension assignée d'isolement Ui                                                                | 800 V   |
| Max. rated operational voltage Ue with AC 50/60Hz                                              | 690 V   |
| power loss [W] / maximum                                                                       | 0.6 W   |
| Active power loss / for rated value of the current / at AC / in hot operating state / per pole | 0.2 W   |
| mechanical service life (switching cycles) / typical                                           | 20 000  |
| Electrical endurance (switching cycles) / at AC-1 / at 380/415 V 50/60 Hz                      | 12 000  |
| Electrical endurance (switching cycles) / at AC-1 / at 690 V 50/60 Hz                          | 8 000   |
| Neutral conductors / upgradeable/retrofitable                                                  | No      |
| ground fault monitoring version                                                                | Without |
| product function                                                                               |         |
| • communication function                                                                       | Yes     |
| • other measurement function                                                                   | No      |
| net weight                                                                                     | 3.14 kg |

| Current                                          |       |
|--------------------------------------------------|-------|
| Max. rated operational current of the frame size | 160 A |
| Courant permanent assigné Iu                     | 25 A  |
| operating current                                |       |
| • at 40 °C                                       | 25 A  |
| • at 45 °C                                       | 25 A  |
| • at 50 °C                                       | 25 A  |
| • at 55 °C                                       | 25 A  |
| • at 60 °C                                       | 25 A  |

- at 65 °C
- at 70 °C

25 A  
25 A

#### Switching capacity according to IEC 60947

|                                                           |        |
|-----------------------------------------------------------|--------|
| switching capacity class of the circuit breaker           | M      |
| maximum short-circuit current breaking capacity (Icu)     |        |
| • at 240 V                                                | 85 kA  |
| • at 415 V                                                | 55 kA  |
| • at 440 V                                                | 55 kA  |
| • at 500 V                                                | 36 kA  |
| • at 690 V                                                | 2.5 kA |
| operational short-circuit current breaking capacity (Ics) |        |
| • at 240 V                                                | 85 kA  |
| • at 415 V                                                | 55 kA  |
| • at 440 V                                                | 55 kA  |
| • at 500 V                                                | 36 kA  |
| • at 690 V                                                | 2.5 kA |
| short-circuit current making capacity (Icm)               |        |
| • at 240 V                                                | 187 kA |
| • at 415 V                                                | 121 kA |
| • at 440 V                                                | 121 kA |
| • at 500 V                                                | 76 kA  |
| • at 690 V                                                | 3.8 kA |

#### Adjustable parameters

|                                                                         |        |
|-------------------------------------------------------------------------|--------|
| Adjustable response value current / I <sub>g</sub> min.                 | 10 A   |
| Adjustable response value current / I <sub>g</sub> min.                 | 25 A   |
| Adjustable response value current / I <sub>g</sub> min.                 | 0.5    |
| Adjustable response value current / I <sub>g</sub> min.                 | 25     |
| Adjustable response value current / I <sub>g</sub> min.                 | 15 A   |
| Adjustable response value current / I <sub>g</sub> min.                 | 250 A  |
| Short-term delayed / tripping switchable / I <sub>2t</sub> =ON/OFF      | Yes    |
| Adjustable response value current / I <sub>g</sub> min.                 | 0.05 s |
| Adjustable response value current / I <sub>g</sub> min.                 | 0.5 s  |
| Adjustable response value current / I <sub>g</sub> min.                 | 0.05 s |
| Adjustable response value current / I <sub>g</sub> min.                 | 0.5 s  |
| Adjustable response value current / I <sub>i</sub> min.                 | 38 A   |
| Adjustable response value current / I <sub>i</sub> max.                 | 300 A  |
| Ground fault protection / tripping switchable / I <sub>2t</sub> =ON/OFF | No     |

#### Mechanical Design

|             |        |
|-------------|--------|
| height [in] | 7.1 in |
|-------------|--------|

|            |        |
|------------|--------|
| Height     | 181 mm |
| width [in] | 5.5 in |
| Width      | 140 mm |
| depth [in] | 3.4 in |
| depth      | 86 mm  |

#### Connections

|                                                                                 |                           |
|---------------------------------------------------------------------------------|---------------------------|
| arrangement of electrical connectors / for main current circuit                 | Front terminal            |
| type of electrical connection / for main current circuit                        | double-sided box terminal |
| Type of connectable conductor cross-section, round conductor terminal, stranded | 1 x (6-120 mm²)           |

#### Auxiliary circuit

|                                                |   |
|------------------------------------------------|---|
| number of CO contacts / for auxiliary contacts | 0 |
|------------------------------------------------|---|

#### Accessories

|                                            |     |
|--------------------------------------------|-----|
| product extension / optional / motor drive | Yes |
|--------------------------------------------|-----|

#### Environmental conditions

|                                    |        |
|------------------------------------|--------|
| protection class IP / on the front | IP40   |
| ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

#### Certificates

|                                         |   |
|-----------------------------------------|---|
| reference code / acc. to DIN EN 81346-2 | Q |
|-----------------------------------------|---|

| General Product Approval                                                                 |                                                                                          |                                                                                         |                               |                                                                                            | EMC                                                                                        |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-------------------------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| <br>CCC | <br>VDE | <br>CB | <a href="#">Miscellaneous</a> | <br>EAC | <br>RCM |

| Declaration of Conformity                                                                     | Test Certificates                                  |                               |                                          | Shipping Approval                                                                          |                                                                                                       |
|-----------------------------------------------------------------------------------------------|----------------------------------------------------|-------------------------------|------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| <br>EG-Konf. | <a href="#">Type Test Certificates/Test Report</a> | <a href="#">Miscellaneous</a> | <a href="#">Special Test Certificate</a> | <br>ABS | <br>BUREAU VERITAS |

| Shipping Approval                                                                        | other                                                                                     |                                                    |                                          |                               |  |
|------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|----------------------------------------------------|------------------------------------------|-------------------------------|--|
| <br>LRS | <br>RMRS | <a href="#">CCS / China Classification Society</a> | <a href="#">Manufacturer Declaration</a> | <a href="#">Miscellaneous</a> |  |

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2125-5JP46-0AA0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2125-5JP46-0AA0>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2125-5JP46-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2125-5JP46-0AA0)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>



last modified:

10/30/2020