

PRODUCT-DETAILS

F202 F-25/0.03

F202 F-25/0.03 Residual Current Circuit Breaker



| General Information | |
|-----------------------|--|
| Extended Product Type | F202 F-25/0.03 |
| Product ID | 2CSF202325R1250 |
| EAN | 8012542992738 |
| Catalog Description | F202 F-25/0.03 Residual Current Circuit Breaker |
| Long Description | The RCCBs F200 series assures protection to people and installations against fault current to earth. Type F offers the same range of protection and functionality as an RCCB Type A APR, this means that they detect sinusoidal AC currents as well as pulsating DC currents. |

| Technical | |
|---|----------------------------------|
| Standards | IEC/EN 61008 IEC/EN 62423 |
| Product Name | Residual Current Circuit Breaker |
| Type of Residual Current | F type |
| Rated Voltage (U _r) | 230 V |
| Rated Operational Voltage | 230 V |
| Rated Insulation Voltage (U ₁) | 500 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 4 kV |
| Input Voltage Type | AC |
| Rated Current (In) | 25 A |
| Rated Residual Current | 30 mA |

| Rated Conditional Short- Circuit Current (I _{nc}) | 10 kA |
|---|--|
| Rated Service Short- Circuit Breaking Capacity (I _{cs}) | 1 kA |
| Maximum Surge Current | 4 kA |
| Rated Frequency (f) | 50 / 60 Hz |
| Power Loss | at Rated Operating Conditions per Pole 1 W |
| Power Supply Connection | Arbitrary |
| Electrical Endurance | 10000 cycle |
| Number of Poles | 2 |
| Operating Characteristic | Instantaneous |
| Mounting Type | DIN rail |
| Options Provided | None |
| Accessories Available | Yes |
| Connecting Capacity | Busbar 10 mm² Rigid 25 25 mm² Flexible 25 25 mm² |
| Rated Cross-Section | 4 - Multi-Wired 025 mm² 1 - Solid-Core 2525 mm² |

| Environmental | |
|------------------------------|-----------------------------------|
| Ambient Temperature | -2555 °C |
| Ambient Air Temperature | Operation -2555 °C |
| Degree of Protection | IP2X |
| Pollution Degree | 2 |
| RoHS Status | Following EU Directive 2011/65/EU |
| Environmental Information | Refer to RoHS |

| Technical UL/CSA | |
|-----------------------|--------|
| Short-Circuit Current | 0.03 A |
| Rating (SCCR) | |

| Dimensions | |
|--|----------|
| Width in Number of Modular Spacings | 2 |
| Product Net Width | 0.035 m |
| Product Net Height | 0.085 m |
| Product Net Depth / Length | 0.069 m |
| Product Net Weight | 0.200 kg |
| Built-In Depth (t ₂) | 69 mm |

| Container Information | |
|---------------------------------|-------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 80 mm |
| Package Level 1 Height | 41 mm |
| Package Level 1 Depth / Length | 94 mm |
| Package Level 1 Gross Weight | 0.235 kg |

Package Level 1 EAN 8012542992738

| Ordering | |
|-------------------------|------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85363030 |
| Country of Origin | Italy (IT) |
| Selling Unit of Measure | piece |

| Certificates and Declarations (Document Nur | nber) |
|---|-----------------|
| Declaration of Conformity - CE | 9AKK106713A5612 |
| Environmental Information | Refer to RoHS |
| Instructions and Manuals | 9AKK107991A6127 |
| RoHS Information | 2CSC423001K2702 |

| Popular Downloads | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107991A8329 |
| Instructions and Manuals | 9AKK107991A6127 |

| Classifications | |
|-------------------------------|---|
| ETIM 6 | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 7 | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 8 | EC000003 - Residual current circuit breaker (RCCB) |
| EPLAN Catalog Tree | Electrical engineering / Protection devices / Ground fault current circuit breaker |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85363030 |
| Object Classification Code | F |

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Residual\ Current\ Devices\ RCDs\ \rightarrow\ Residual\ Current\ Devices\ RCDs$

F202 F-25/0.03 4

