

PRODUCT-DETAILS

U32MM

U32MM Compact distribution board



General Information

Extended Product Type	U32MM
Product ID	2CPX030088R9999
EAN	4011617300885
Catalog Description	U32MM Compact distribution board

Long Description

Compact distribution board, series U, partly assembled cabinet, for the internal use, with closed doorframe and door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP31, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, powder-coated, in RAL 9016, enclosure out of sheet steel, metal door, door out of sheet steel, in RAL 9016, with Standard closure, door opening angle 130 degree, door hinge right or left, cable entry on top via nipple flange included, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 534 x 560 x 120. Shutter frame dimensions in mm (H x W x D): 544 x 604 x 27, Grid unit 3 GU, panel width 2, 3-rows, Space units 36, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, RAL 7035, with N/PE Quick-terminal, cable fastening rail integrated, Assembled with distribution module + multimedia module, device support removable

Technical

Standards	DIN EN 61439-3
Product Name	Compact distribution board
Rated Operational Voltage	Maximum 400 V
Operational Voltage	400 V
Rated Current (I_n)	125 A
Power Loss	$\Delta t = 20K$ 33.1 W $\Delta t = 25K$ 43.7 W $\Delta t = 30K$ 54.8 W

Number of Rows	3
Closure Type	Turn Handle
Configuration Type	Assembled with distribution module + multimedia module
Cover Plate Type	Door
Enclosure Type	compact distribution boards
Mounting Type	Flush-mounted
Door Type	Single
Housing Material	Steel
Cover Style	Closed
DIN Place Units	36
RAL Number	RAL 9016 - Traffic White
Color	Traffic white
Terminal Type	Quick-Terminal

Environmental

Degree of Protection	IP31
Protection Class	Isolated

Dimensions

Width in Number of Modular Spacings	24
Product Net Width	560 mm
Product Net Height	534 mm
Product Net Depth / Length	120 mm
Product Net Weight	12.611 kg
Built-In Depth (t ₂)	120 mm

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	640.000 mm
Package Level 1 Height	175.000 mm
Package Level 1 Depth / Length	580.000 mm
Package Level 1 Gross Weight	13.115 kg
Package Level 1 EAN	4011617300885
Package Level 2 Units	pallet (lift) 20 piece
Package Level 2 Width	830.000 mm
Package Level 2 Height	1640.000 mm
Package Level 2 Depth / Length	1200.000 mm

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85381000
Country of Origin	Germany (DE)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107992A8144
Instructions and Manuals	2CPC100502M5601 2CPC130114M5601

Popular Downloads

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101 2CPC000377C0101 2CPC000003B0101
Instructions and Manuals	2CPC100502M5601 2CPC130114M5601

Classifications

ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
ETIM 8	EC000214 - Small distribution board
EPLAN Catalog Tree	Mechanics / Housings / General
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85381000
Object Classification Code	U

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Compact Distribution Boards - Modules Assembled

