## Junction box 120 mm air-tight



## Junction box Ø 120 mm O-range ECON®

- · Air-tight design with sealing membranes
- for 2 electrical circuits through separator wall 9073-20
- receptacle for TS 35 standard rail
- with stable holding ring
- · Cutting the installation opening with bi-metal cutter 1082-20 or VARIOCUT 1089-00
- including cover and screws

LUFTDICHT	



Order number:	9273-77
EAN:	4013456548794
For panel thickness	7 - 40 mm
Depth	65 mm
Cut hole Ø	120 mm
Tube entries up to M25	6
Cable entries 3 x 2.5 mm <sup>2</sup> or 5 x 1.5 mm <sup>2</sup>	6
Cable entries $5 \times 2.5 \text{ mm}^2$ or $7 \times 1.5 \text{ mm}^2$	4
Cable entries 3 x 1.5 mm <sup>2</sup>	6
Air-tight	Yes
Halogen-free	Yes
Dispatch	10

Air-tight  $\emptyset$  120 mm junction box with ECON® technology for an energy-efficient electrical installation in accordance with EnEV. Extremely easy fitting thanks to toolless cable and conduit entry. The sealing membranes guarantee permanent air-tightness and at the same time retention of the cable or conduit. The large box volume provides plenty of installation space for various cable connections.

- · Installation in Ø 120 mm cut hole
- · Elastic sealing membrane for guaranteed air-tightness
- · Tool-free cable and conduit entry



