

Product Data Sheet: Earthing and Short-Circuiting Devices (fully insulated) for Low-Voltage Cable Distribution Cabinets



EKS VI 2F KVS KK (745 903)

- Fully insulated (VI), shock-proof version
- Fully equipped kit for cable distribution cabinets
- Other cable lengths can be selected online via the earthing and short-circuiting configurator



Figure without obligation

Figure without obligation

Set – Bestückung:

Pos.	Art.-Nr.	Pos.	Art.-Nr.
1	1x 745 902	5	6x 745 910
3	2x V162LDM	6	1x 745 922
4	3x 745 905		

Nähere Angaben zu den Artikeln
siehe Einzelteile.

Type	EKS VI 2F KVS KK
Part No.	745 903
Variant No. of EaS device	V162LDM
Dimensions	450 x 350 x 110 mm
Standard	EN/IEC 61230 (DIN VDE 0683-100)
Temperature range	–25 °C ... +55 °C
Weight	7 kg
Customs tariff number (Comb. Nomenclature EU)	85369095
GTIN	4013364093577
PU	1 pc(s)

Attention: Please state the relevant Variant No. when ordering.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.