


**PCE data sheet**

article#	<b>245-6xs</b>
article description	<b>CEE-connector 125A 5p 6h IP67 POWER TWIST black</b>
description long	CEE-connector 125A5p 6h IP67 POWER TWIST black housing material: PA6 rated current: 125A number of poles: 5 (3P+N+PE) clock-position: 6h rated voltage/frequency: 200/346V~ - 240/415V~ / 50+60Hz contacts: brass, with lamellar spring (CuBe) connection technology: frame terminals with screws IP protection class: IP66/IP67
GTIN (EAN)	9003399713637
country of origin	AT
customs number	85366990
packaging quantity	2
minimum order quantity	2



ETIM 7.0	EC001320
IEC-amperage	125 A
Number of poles	5
Voltage acc. EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h
Identification colour	Red
RAL-number	9005
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Straight
Cable entry	Swivel
Material	Plastic
Contact material	CuZn
Surface finish contacts	Untreated

a	287 mm
b	124 mm
K (cable Ø)	22,5-50 mm
SW	81 mm
wire flexible	16-50 mm <sup>2</sup>
contact screws	450 Ncm
strain relief	1500 Ncm
dismantling length	100 mm
stripping length	24-27 mm


[www.manufacturer-safety.info](http://www.manufacturer-safety.info)