

# EARTHING & NEUTRAL BUSBAR, TINNED ALUMINUM, 6 CONNECTIONS

### **CATALOG NUMBER**

## EB6AL



Earthing and Neutral Busbars are used to connect several earthing conductors within a panel and can be used in a variety of different applications such as switchgear and control equipment, electrical equipment, for wind and solar power generation and data centers.

#### CERTIFICATIONS



## **FEATURES**

Tinned aluminum bar allows for copper or aluminum conductor connections

Use to connect several earthing conductors

Chamfered holes allow for easy connections

Tin plating is corrosion resistant

Rigid bar

Can be fixed using IRS Angle Support Bracket, DMH Metallic Spacer or DH Distance Holder and Spacer

Quick and easy installation

**RoHS** compliant

## **PRODUCT ATTRIBUTES**

Article Number: 568712

Material: Aluminum

Finish: Tinned

Certification Details: UL® 467

Number of Holes: 8
Conductor Size, IEC: 2.5 - 16 mm <sup>2</sup> Stranded
Conductor Size, UL: #14 - #4 Stranded
Max Current Rating: 85 A
Height: 11.20 mm
Width: 65 mm
Depth: 7.90 mm
Unit Weight: 0.017 kg

## DIAGRAMS



### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

#### North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

#### Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

## APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

Our powerful portfolio of brands. CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER nVent.com © 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of

their respective owners.

nVent reserves the right to change specifications without notice.