

PRODUCT-DETAILS

# 316BS6

316BS6 P 3vodka n st nn , 4p., 16 A, IP44, 6 h



## Obeční informace

Typ	316BS6
Id v robku	2CMA193298R1000
EAN	7392696932981
Katalogov popis	316BS6 P 3vodka n st nn , 4p., 16 A, IP44, 6 h
Detailn <sup>2</sup> popis	Wall mounted inlet, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Red

## Technické údaje

Normy	IEC 60309-1, -2
Funkce	Wall mounted inlet
Vhodn pro	Surface Inlets
Vhodn pro v robek t <sup>2</sup> dy	IEC Industrial Plugs and Sockets
Jmenovit nap t <sup>2</sup> (U <sub>r</sub> )	380 ... 415 V
Jmenovit proud (I <sub>n</sub> )	16 A
Frekvence (f)	50 Hz 60 Hz
Jmenovit frekvence (f)	50 é 60 Hz
Mont n <sup>2</sup> otvory	111x72
Po et p·l	4
N vrh	Surface mounted plug

Plug Angle	Angled
Utahovac <sup>2</sup> moment	WireClamp0.8 N m
Typ p ipojen <sup>2</sup>	Screw
Typ upevn <sup>n</sup>	Angled
Typ ochrany	Splashproof
Clock Position Of Grounding Contact	6 hour
Materi l zapouzd en <sup>2</sup>	Thermoplastic
Materi l pouzdra	Plastic (PA)
Materi l	Plastic
P řidavn informace	3P+E
Doporu en roubov k	PH2
RAL Number	RAL 7012 - Basalt Grey
Barva	Red
Pr ez kabelu/vodi e	1.5 ... 4 mm

### daje vn j řho prost ed<sup>2</sup>

Teplota okol <sup>2</sup>	-25 ... 40 C
Kryt <sup>2</sup>	IP44
Stav RoHS	Following EU Directive 2011/65/EU
Environment In <sup>2</sup> informace	2CMC000056M0000

### Technick daje UL/CSA

Utahovac <sup>2</sup> moment UL/CSA	7.1 in lb
-------------------------------------	-----------

### Rozm ry

ist <sup>2</sup> ka v robku	78 mm
ist v ka v robku	68 mm
ist hloubka v robku	118 mm
ist hmotnost v robku	0.19 kg
Velikost	78X79X124

### Balen<sup>2</sup>

rove balen <sup>2</sup> 1, jednotky	box 10 piece
rove balen <sup>2</sup> 1, <sup>2</sup> ka	154 mm
rove balen <sup>2</sup> 1, v ka	378 mm
rove balen <sup>2</sup> 1, d lka	182 mm
rove balen <sup>2</sup> 1, hrub hmotnost	1.9 kg
rove balen <sup>2</sup> 1, EAN	7392696662987
rove balen <sup>2</sup> 2, jednotky	pallet (lift) 450 piece
rove balen <sup>2</sup> 2, <sup>2</sup> ka	800 mm
rove balen <sup>2</sup> 2, v ka	900 mm
rove balen <sup>2</sup> 2, d lka	1200 mm
rove balen <sup>2</sup> 2, hrub hmotnost	875 kg

rovo balen<sup>2</sup>, EAN

7392696080262

**Objednac<sup>2</sup> daje**

Minim In <sup>2</sup> objednac <sup>2</sup> mno stv <sup>2</sup>	10 piece
řslo celnřho sazebnřku	85366990
E-Number (Finland)	2421513
E-Number (Norway)	1542373
E-Number (Sweden)	E2417168
Zem p vodu	Czech Republic (CZ)

**Certifik ty a prohl en<sup>2</sup> ( řsla dokument )**

Prohl en <sup>2</sup>	2CMC700005D0001
Prohl en <sup>2</sup> o shod - CE	2CMC700005D0001
Environment In <sup>2</sup> informace	2CMC000056M0000
Pokyny a p řtu ky	2CMC700014C0016
REACH Declaration	2CMC700005D0001
Informace RoHS	2CMC700005D0001
Certifik t SEMKO	2CHC660161X0201

**Dokumenty ke sta en<sup>2</sup>**

List s daji, technick informace	2CMC700006C0201
Pokyny a p řtu ky	2CMC700014C0016
Mechanick v kresy	9AKK107680A3025

**Klasifikace**

ETIM 7	EC001319 - CEE plug for mounting on machines and equipment
ETIM 8	EC001319 - CEE appliance inlet
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85366990
UNSPSC	39121406
Trřda eClass	27440519
IDEA Granular Category Code (IGCC)	4537 >> Round plug/flat receptacle

**Kategorie**

P řstroje a rozv d e nřzk ho nap tř → Pr myslov vidlice a z suvky → Easy &amp; Safe → Surface Inlets

