

PRODUCT-DETAILS

# SBA-F-2.1.1

## SBA-F-2.1.1 Sensor/Blind actuator 2/1g



### Obecné informace

Typ	SBA-F-2.1.1
Id výrobku	2CKA006220A0129
EAN	4011395180174
Katalogový popis	SBA-F-2.1.1 Sensor/Blind actuator 2/1g

Detailní popis	<p>For controlling blind or awning motors. With integrated blind actuator. Blind function is available also without prior programming (left sensor channel is pre-configured). Configuration can be changed later via the web interface (groups, scenes, etc.). The right sensor channel for programming additional functions (groups, scenes, etc.). For contacting 2gang rocker 6230-2x-xxx, 6231-2x-xxx, 6232-2x-xxx, 6233-2x-xxx and 6234-2x-xxx. The bus can be connected via enclosed terminal block. When installing in the flush-mounted box, a spatial division between the bus cable and 127 V/230 V installation cable is to be adhered to! If this minimum distance is not possible, use electronic boxes or insulating tubes.</p>
----------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Technické údaje

Druh proudu	AC
Jmenovitý proud ( $I_n$ )	4 A
Maximum Switching Current	Resistive Load 4 A
Maximum Switching Power	920 W

Počet výstupů	2
Compatible Bus Systems	free@home
Výrobní řada	ABB-free@home®
Druh zátěže	Operation mode Blind
Typ upevnění	Flush Mounted
Number of Batteries	0

## Údaje vnějšího prostředí

Teplota okolního vzduchu	Operation -5 ... +45 °C
Krytí	IP20
Stav RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## Rozměry

Čistá hmotnost výrobku	55 g
Instalační hloubka (t <sub>2</sub> )	32 mm

## Balení

Úroveň balení 1, jednotky	carton 1 piece
Úroveň balení 1, šířka	92 mm
Úroveň balení 1, výška	58 mm
Úroveň balení 1, délka	78 mm
Úroveň balení 1, hrubá hmotnost	0.074 kg
Úroveň balení 1, EAN	4011395180174

## Objednací údaje

Minimální objednávková množství	1 piece
Číslo celního sazebníku	85389091
E-Number (Sweden)	1701060
Země původu	Germany (DE)

## Certifikáty a prohlášení (Číslo dokumentů)

Prohlášení o shodě - CE	2CKA100000E1374
Pokyny a příručky	No document needed
REACH Declaration	2CKA309999E9999
Informace RoHS	2CKA200000E4922

## Dokumenty ke stažení

List s údaji, technické	2CKA001173B8557
-------------------------	-----------------

informace

Pokyny a příručky

No document needed

---

## Klasifikace

ETIM 7	EC001330 - Shutting actuator for bus system
ETIM 8	EC001330 - Shutting actuator for bus system
EPLAN - stromová architektura katalogu	Electrical engineering / Sensor, switch, and pushbutton / Switch , pushbutton
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8538 90 91
Trída eClass	V11.0 : 27143128

---

## Kategorie

Přístroje a rozváděče nízkého napětí → Home and Building Automation → free@home → Shading Control → Blind Actuators 230 V AC

