

PRODUCT-DETAILS

## 363MHS6

363MHS 6 Z<sup>RS</sup>uvka s blokovan<sup>u</sup>m vyp<sup>o</sup>naTem,  
horizont<sup>o</sup>n<sup>o</sup>, 4p., 63 A, IP44, 6 h



### Obecn<sup>o</sup> informace

Typ	363MHS6
Id výrobku	2CMA167721R1000
EAN	7392696677219
Katalogový popis	363MHS6 Z <sup>RS</sup> uvka s blokovan <sup>u</sup> m vyp <sup>o</sup> naTem, horizont <sup>o</sup> n <sup>o</sup> , 4p., 63 A, IP44, 6 h
Detailný popis	Switched Interlocked Socket Outlet, horizontal, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Red

### Technick<sup>o</sup> údaje

Normy	IEC 60309-1, -2, -4
Funkce	Switched interlocked socket outlet, horizontal
D <sup>o</sup> funkce	Cable entry, knock-outs 2x $\phi$ 32mm
Vhodn <sup>o</sup> pro	Switched Interlocked Socket Outlets, Horizontal
Vhodn <sup>o</sup> pro výrobek t <sup>o</sup> dy	IEC Industrial Plugs and Sockets
J menovit <sup>o</sup> napat <sup>o</sup> (U <sub>r</sub> )	380 ... 415 V
J menovit <sup>o</sup> proud (I <sub>n</sub> )	63 A
Frekvence (f)	50 Hz 60 Hz
Mont <sup>o</sup> otvory	152x132
Počet p <sup>o</sup> lu	4
Utahovac <sup>o</sup> moment	WireClamp3.5 Nm

Typ pŕipojen°	S crew
Typ upevnan°	Horizontal
Typ ochrany	Switched Interlocked
Switch Type	Mechanical Locking
Type of Fastening	Inner Lying Mounting
Clock Position Of Grounding Contact	6 hour
Mounting Orientation	Horizontal
Materi° z apouzden°	Thermoplastic polyester (PBT)
Materi° pouzdra	Thermoplastic (PBT)
Materi°	Plastic
Pŕidavn° informace	3P+E
DoporuTenwprubov°k	PH2
M°sto vstupu kabelu	Top and bottom
PoTet vustupwkabelu na stranu	1xd 32
Model Number	Surface mounted (plaster)
RAL Number	RAL 7001 - Silver Grey
Barva	Red
Pruprez kabelu/vodiTe	6 ... 25 mm <sup>2</sup>

### Qdaje vnajŕho prostŕed°

Teplota okol°	-25 ... 40 °C
Kryt°	IP44
Stav RoHS	Following EU Directive 2011/65/EU
Environment°n° informace	2C MC 000057M0000

### Technick° ŕdaje UL/CSA

Utahovac° moment UL/CSA	31 in <sup>lb</sup>
-------------------------	---------------------

### Rozmary

Cist°pŕka vrobku	206 mm
Cist°vupka vrobku	168 mm
Cist°hloubka vrobku	168 mm
Cist°hmotnost vrobku	2 kg
Velikost	168X206X168

### Balen°

Qrovek balen° 1, jednotky	box 1 piece
Qrovek balen° 1, pŕka	180 mm
Qrovek balen° 1, vupka	180 mm
Qrovek balen° 1, d°lka	215 mm
Qrovek balen° 1, hrub° hmotnost	2 kg
Qrovek balen° 1, EAN	7392696677219
Qrovek balen° 2, jednotky	pallet (lift) 84 piece

Ørovek balen° 2, p°jka	800 mm
Ørovek balen° 2, vupka	900 mm
Ørovek balen° 2, d°jka	1200 mm
Ørovek balen° 2, hrub° hmotnost	188 kg
Ørovek balen° 2, EAN	7392696074599

## Objednac° sdaje

Minim°ln° objednac° mnoztv°	1 piece
C°slo celn°ho sazebn°ku	85366990
E-Number (Finland)	2421438
E-Number (Norway)	1564846
E-Number (Sweden)	E 2416869
Zema puvodu	Czech Republic (CZ)

## Certifik°ty a prohl°pen° (C°sla dokumentu)

Prohl°pen°	2C MC 700005D0001
Prohl°pen° o shoda - CE	2C MC 700005D0001
Environment°ln° informace	2C MC 000057M0000
Pokyny a p°pruTky	2C MC 000031M0001
REACH Declaration	2C MC 700005D0001
Informace RoHS	2C MC 700005D0001
Certifik°t SEMKO	2C HC 660036X0201

## Dokumenty ke staten°

List s sdaji, technick° informace	2C MC 000031M0001
N°vod k instalaci	2C MC 000031M0001
Pokyny a p°pruTky	2C MC 000031M0001
Mechanick° vukresy	9AKK 107991A3885

## Klasifikace

ETIM 7	EC001324 - CEE socket outlet, disconnectable, with fuse
ETIM 8	EC001324 - CEE socket outlet, disconnectable, with fuse
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85366990
UNSPSC	39121406
Tr°da eClass	27440510
IDEA Granular Category Code (IGCC)	4536 >> Electrical receptacles

---

## Kategorie

---

Prístroje a rozváděče nízkého napětí " Průmyslové vidlice a zásuvky " Critical & Safe " Switched Interlocked Socket Outlets

