

# KB 26 Cable bracket 30450

CE  
6/2022

## Areas of application:

For the conduit laying of non-metallic sheathed cables. The KB 26 cable bracket can hold up to 26 cables (3 x 1.5 mm<sup>2</sup>).

## Installation Guide:

- Drill a 6 mm Ø hole
- Insert the KB into the drill-hole
- Insert the cable/s into the gap between the wall and ceiling.
- If required up to two EC clamps, in any pipe diameter size can be attached directly to the KB

## Product details:

Colour	light grey
Content box	50
Clamping range mm	200

## Product benefits/properties:

Perfect and quick laying of multiple cables directly on the ceiling. Insert the KB with minimal effort, then lay the cable. The KBs own internal stress is sufficient to ensure the cable is mounted firmly even against high temperature fluctuations. Unique attachment option for the EC Euro Clip - for retrofitting of a pipe or the separate laying of different cables - without the need for drilling.

## Technical data:

Material	PP, UV stabilised Temperature range: -10 °C up to +85 °C silicon-free <b>Material tested according OVR R14 (LSFOH)</b>
----------	---

Weight per piece 10,60 g

Max. recd. load 150.4 N concrete

Breaking load 376 N (37 kg) concrete

GTIN (EAN)



The KB cable brackets have been developed for the section installation of wiring harnesses.



Schnabl Stecktechnik GmbH, Bahnhofplatz 1, po box 63, 3100 St. Pölten, Austria  
Telephone +43 2742 22167-0. office@schnabl.works. www.schnabl.works

