

SH 40 cable holder 30530

CE
6/2022

Areas of application:

For the multiple carrying of up to 40 sheathed cables with Ø 10 mm.

Installation Guide:

- Drill a 6mm Ø hole
- Put the SH in the drill hole
- Insert cable/s into the SH
- Close the locking tab of the SH
- If required an EC clamp, in any pipe diameter size can be attached directly to the SH

Product details:

Colour	light grey
Content box	100
Cable capacity	max. 40 NYM 3 x 1.5 mm ²

Product benefits/properties:

Even when installed, the cable holder can be easily opened and closed again. This allows cables to be easily added and removed. In tight areas like intermediate ceilings, above ventilating or sprinkler pipes, the SH 40 can be rotated up to 90° and installed with our Dowel Fastening Nail - DSN through the slotted hole. There is the option to fit the Schnabl EC Euro clip on to the SH cable holder.

Technical data:

Material	PP, UV stabilised Temperature range: -10 °C up to +85 °C silicon-free Material tested according OVR R14 (LSFOH)
Weight per piece	17,00 g
Max. recd. load	130.4 N concrete
Breaking load	326 N (32 kg) concrete
GTIN (EAN)	9 008439 805303



The SH holder forms a closed ring around the sheathed cables and can be re-opened using a handle.



Schnabl Stecktechnik GmbH, Bahnhofplatz 1, po box 63, 3100 St. Pölten, Austria
Telephone +43 2742 22167-0. office@schnabl.works. www.schnabl.works

