

FLEXBUS ALUMINUM PERFORATED PROFILE

CATALOG NUMBER

FLEXALPROF2M



CERTIFICATIONS



FEATURES

Optional brackets are available

Factory-punched head holes for quick assembly

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 508100

Material: Aluminum

A: 12.5 mm

Hole Size: 8 mm

Height: 15 mm

Length: 2000 mm

Width: 35 mm


Unit Weight: 0.9 kg

ADDITIONAL PRODUCT DETAILS

Support kit and aluminum profile are sold separately.

When cable tray is used, we recommend installing a Flexbus Support at each extremity, in order to protect the Flexbus Conductor against potential sharp edges of the cable tray.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europe Netherlands: +31 800-0200135 France: +33 800 901 793	Europe Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--