

EARTHING & NEUTRAL DOUBLE BUSBAR, NICKEL PLATED BRASS, 2X130 CONNECTIONS

CATALOG NUMBER

EB2X130



CERTIFICATIONS



FEATURES

Use to connect several earthing conductors

Chamfered holes allow for easy connections

Main terminal clamp available for thicker conductors

Support bracket available for attaching busbar to DIN rail

Nickel plating is corrosion resistant

Rigid bar

Cut to length as needed

Quick and easy installation

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 568674

Material: Brass

Finish: Nickel Plated

Number of Connections: 260

Conductor Size, IEC: 1.5 - 25 mm² Stranded

Max Current Rating: 200 A

Cross Section: 225 mm²

Depth: 15 mm

Height: 15 mm

Width: 1000 mm

Hole Size: 6.5 mm

Thread Size: M5

A: 7 mm

Torque: 2 N·m

Unit Weight: 1.59 kg

Complies With: IEC® 60998-2-1

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER