

FLEXBUS SHEAR

CATALOG NUMBER





FEATURES

Shear is used to cut the FleXbus Conductor over length Favorable lever ratio and optimized cutting edge geometry require less effort Adjustable bolted joint, self-retaining screw Precision-ground, hardened blades Allows for a clean, smooth cut without causing crushing or deformation Guard provides added safety High-grade special tool steel, forged, oil-hardened

PRODUCT ATTRIBUTES

Article Number: 508173

Material: Steel

Unit Weight: 0.32 kg

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europe

nVent.com

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

HOFFMAN

APAC

RAYCHEM SCHROFF

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

Our powerful portfolio of brands:

CADDY ERICO

nVent reserves the right to change specifications without notice.

2