

# ADJUSTABLE I-BEAM ADAPTER, EG, 6-19 MM FLANGE, 100-365 MM

### **CATALOG NUMBER**

# CSBS4



#### **CERTIFICATIONS**









# **FEATURES**

No loose parts

No assembly required

Snap-off bolt head helps enable easy installation and inspection of seismic sway braces

Meets NFPA®-13 requirements for seismic sway bracing

FM® Specification Tested

### **PRODUCT ATTRIBUTES**

Article Number: 404508

Material: Steel

Finish: Electrogalvanized

Flange Thickness: 6 - 19 mm

A: 100 - 365 mm

Rod Size 1: 3/8"


Width: 92 mm

# ADDITIONAL PRODUCT DETAILS

Structure Attachment and Brace Member are not included.

FM Loads									
Part Number	Horizontal Capacity per Installation Angle from Vertical								
	Perpendicular to Structure				Parallel to Structure				
	30°- 44°	45°- 59°	60°- 74°	75°- 90°	30°- 44°	45°- 59°	60°- 74°	75°- 90°	
CSBS3	5240 N	9830 N	12580 N	13070 N	3640 N	6130 N	9250 N	13380 N	
CSBS4	5240 N	9830 N	12580 N	13070 N	3640 N	6130 N	9250 N	13380 N	
CSBS5	5420 N	9510 N	11470 N	12760 N	4890 N	8090 N	9740 N	11920 N	

UL Loads							
Part Number	Structure Attachment Fitting	Flange Thickness	Brace Member	Load Rating			
	CSBU1	6 - 8 mm	DN25 - DN50 Sch. 40 NPS	6672 N			
	CSBUT	8 - 19 mm	DN25 - DN50 SCII. 40 NPS	7561 N			
SBS3		CSB12CBL	CSB12CBL	1859 N			
	CSBURC12	6 - 19 mm	CSB18CBL	3434 N			
			CSB36CBL	4893 N			
	00011	6 - 8 mm	DN05 DN50 0-1- 40 ND0	6672 N			
	CSBU1	8 - 19 mm	DN25 - DN50 Sch. 40 NPS	7561 N			
SBS4			CSB12CBL	1859 N			
	CSBURC12	6 - 19 mm	CSB18CBL	3434 N			
	CSB36CBL	CSB36CBL	4893 N				
CSBS5	CSBU1	6 - 19 mm	DN25 DN50 Sch. 40 NPS	7561 N			
			CSB12CBL	1859 N			
	CSBURC12	6 - 19 mm	CSB18CBL	3434 N			
			CSB36CBL	4893 N			





#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

#### **North America**

+1.800.753.9221

Option 1 – Customer Care

Option 2 - Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

**Europe** 

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN RAYCHEM SCHROFF** 

nVent.com
TRACER