

6.2 ZÁSUVKOVÉ SKŘÍŇE A STAVENIŠTNÍ ROZVÁDĚČE V KRYTÍ IP54 - IP65

6.2 WIRED ENCLOSURES WITH IP65 SOCKETS



1

Obj. č.	Zásuvky	Chránič	Jističe
TOP v310	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v310-6kA	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1



Rozměry (mm)	
Výška	398
Šířka	266
Hloubka	153

Použité pouzdro: 3959

Počet modulů: 12

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



2



3

Obj. č.	Zásuvky	Chránič	Jističe
TOP v3106	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v3106-6kA	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1



Rozměry (mm)	
Výška	398
Šířka	266
Hloubka	153

Použité pouzdro: 3959

Počet modulů: 12

Stupeň krytí: IP65

Normy: EN 62208, IEC 61439-3



4



5

Obj. č.	Zásuvky	Chránič	Jističe
v380	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	Pouze vydrátovaná	
v385	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v385-6kA	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1
v3852	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	1x PL7 B32/3 1x PL7 B16/3 1x PL7 B16/1
v3852-6kA	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	1x PL6 B32/3 1x PL6 B16/3 1x PL6 B16/1
EKO v390	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B16/3 2x PL7 B16/1
EKO v390-6kA	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B16/3 2x PL6 B16/1



Rozměry (mm)	
Výška	330
Šířka	215
Hloubka	155

Použité pouzdro: 3958

Počet modulů: 9

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



6



7

EKO - Zásuvková skříň je určena jen pro malé proudové odběry
- Zásuvková skříň není vhodná do průmyslu
- 400 V zásuvky mají společný jistič



8

Obj. č.	Zásuvky	Chránič	Jističe
v598	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B32/3 1x PL7 B16/3 2x PL7 B16/1
v598-6kA	1x 400 V / 32 A / 5p 1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B32/3 1x PL6 B16/3 2x PL6 B16/1



Rozměry (mm)	
Výška	330
Šířka	330
Hloubka	155

Použité pouzdro: 3974

Počet modulů: 16

Stupeň krytí: IP54

Normy: EN 62208, IEC 61439-3



9



10