

6.2 ZÁSUVKOVÉ SKŘÍŇE A STAVENIŠTNÍ ROZVÁDĚČE V KRYTÍ IP54 - IP65

6.2 WIRED ENCLOSURES WITH IP65 SOCKETS



1

Obj. č.	Zásuvky	Chránič	Jističe
v780	12x 230 V / 16 A / 3p	Pouze vydrátovaná	
v785	12x 230 V / 16 A / 3p	-	6x PL7 B16/1
v785-6kA	12x 230 V / 16 A / 3p	-	6x PL6 B16/1
v790	12x 230 V / 16 A / 3p	-	12x PL7 B16/1
v790-6kA	12x 230 V / 16 A / 3p	-	12x PL6 B16/1
v792	12x 230 V / 16 A / 3p	1x PF7 40/4/003	6x PL7 B16/1
v792-6kA	12x 230 V / 16 A / 3p	1x PF6 40/4/003	6x PL6 B16/1
v795	12x 230 V / 16 A / 3p	1x PF7 40/4/003	9x PL7 B16/1
v795-6kA	12x 230 V / 16 A / 3p	1x PF6 40/4/003	9x PL6 B16/1



Rozměry (mm)	
Výška	500
Šířka	330
Hloubka	155

Použité pouzdro: 3952
Počet modulů: 16
Stupeň krytí: IP54
Normy: EN 62208, IEC 61439-3



2



3

Obj. č.	Zásuvky	Chránič	Jističe
v015	1x 400 V / 16 A / 5p	Pouze vydrátovaná	
v018	1x 400 V / 16 A / 5p	-	1x PL7 B16/3
v018-6kA	1x 400 V / 16 A / 5p	-	1x PL6 B16/3
v020	1x 400 V / 16 A / 5p	1x PF7 40/4/003	1x PL7 B16/3
v020-6kA	1x 400 V / 16 A / 5p	1x PF6 40/4/003	1x PL6 B16/3



Rozměry (mm)	
Výška	245
Šířka	215
Hloubka	155

Použité pouzdro: 3957
Počet modulů: 9
Stupeň krytí: IP54
Normy: EN 62208, IEC 61439-3



4



5

Obj. č.	Zásuvky	Chránič	Jističe
v065	1x 400 V / 16 A / 5p 1x 230 V / 16 A / 3p	Pouze vydrátovaná	
v070	1x 400 V / 16 A / 5p 1x 230 V / 16 A / 3p	-	1x PL7 B16/3 1x PL7 B16/1
v070-6kA	1x 400 V / 16 A / 5p 1x 230 V / 16 A / 3p	-	1x PL6 B16/3 1x PL6 B16/1
v075	1x 400 V / 16 A / 5p 1x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B16/3 1x PL7 B16/1
v075-6kA	1x 400 V / 16 A / 5p 1x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B16/3 1x PL6 B16/1



Rozměry (mm)	
Výška	245
Šířka	215
Hloubka	155

Použité pouzdro: 3957
Počet modulů: 9
Stupeň krytí: IP54
Normy: EN 62208, IEC 61439-3



6



7

Obj. č.	Zásuvky	Chránič	Jističe
v155	1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	Pouze vydrátovaná	
v1601	1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	1x PL7 B16/3 1x PL7 B16/1
v1601-6kA	1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	1x PL6 B16/3 1x PL6 B16/1
v160	1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	1x PL7 B16/3 2x PL7 B16/1
v160-6kA	1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	-	1x PL6 B16/3 2x PL6 B16/1
v1652	1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B16/3 1x PL7 B16/1
v1652-6kA	1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B16/3 1x PL6 B16/1
v165	1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF7 40/4/003	1x PL7 B16/3 2x PL7 B16/1
v165-6kA	1x 400 V / 16 A / 5p 2x 230 V / 16 A / 3p	1x PF6 40/4/003	1x PL6 B16/3 2x PL6 B16/1



Rozměry (mm)	
Výška	245
Šířka	215
Hloubka	155

Použité pouzdro: 3957
Počet modulů: 9
Stupeň krytí: IP54
Normy: EN 62208, IEC 61439-3



8



9



10

TOP