

EAN Code: 3606480504143



Main

Switch application	Photovoltaic inverter protection
Range of product	SW60
Product or component type	Switch disconnecter
Device short name	SW60-DC
Poles description	2P
Utilisation category	DC-21A
Suitability for isolation	Yes conforming to EN/IEC 60947-3

Complementary

[Ie] rated operational current	50 A DC-21A 1000 V DC 40 °C 63 A DC-21A 1000 V DC 5 °C 61 A DC-21A 1000 V DC 10 °C 60 A DC-21A 1000 V DC 15 °C 58 A DC-21A 1000 V DC 20 °C 56 A DC-21A 1000 V DC 25 °C 54 A DC-21A 1000 V DC 30 °C 52 A DC-21A 1000 V DC 35 °C 48 A DC-21A 1000 V DC 45 °C 46 A DC-21A 1000 V DC 50 °C 41 A DC-21A 1000 V DC 60 °C 35 A DC-21A 1000 V DC 70 °C
Voltage Drop	251 mV 5.02 mOhm 12.54 W 50 A
[Ui] rated insulation voltage	1000 V DC
[Uimp] rated impulse withstand voltage	6 kV
Control type	Toggle
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	8
Height	132.7 mm
Width	72 mm
Depth	77.4 mm
Net weight	0.53 kg
Colour	White
Mechanical durability	20000 cycles
Electrical durability	3000 cycles
Connections - terminals	Tunnel terminal (upside) 1...35 mm ² rigid Tunnel terminal (upside) 1...25 mm ² flexible Pre-wired cable (downside)
Tightening torque	3.5 N.m
Compatibility code	SW60-DC

Environment

Standards	EN/IEC 60947-3
Pollution degree	2
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------