



Main

Range of product	ARGUS movement detector
Range	ARGUS
Product or component type	Movement detector
Device application	Light control
Sensor type	PIR
Load type	Incandescent lamp: 2000 W - 230 V, AC LED lamp: with integrated ballast 8 x 58 W, 176 µF - 230 V, AC Fluorescent lamp: cos phi = 0.5 1000 W - 230 V, AC
Colour tint	Polar white
Colour code	RAL 9003
Type of packing	Carton

Complementary

Clamping connection capacity	$\leq 2.5 \text{ mm}^2$
Inrush current	600 A for 20 µs
Provided equipment	1 x surface box 1 x sensor 1 x surface cover 1 x screws 1 x user manual 1 x lens mask
Depth	65 mm
Width	121 mm
Height	121 mm
Diameter	121 mm
Quantity per set	Set of 1
Connections - terminals	Screwless terminals
[Ue] rated operational voltage	220...240 V AC
Network frequency	50/60 Hz
Input compatibility	Extension input for push-buttons and electronic insert
Input function	External trigger

Protection type	External fuse
Type of setting	Time adjustment Light sensitivity adjustable
Function available	Brightness adjustment Teach mode Time adjustment Pulse function Dazzle guard Presence detector switch-off logic
Display type	LED
Time delay	5 s...15 min
Light intensity adjustment	2...1000 lux
Horizontal detection angle	0...360 °
Detection range	Radius: 20 m
Material	Thermoplastic glossy
Device mounting	Ceiling
Mounting height	2.5 m

Environment

IP degree of protection	IP54
Ambient air temperature for operation	-20...50 °C
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins