

SX25-ISDN-BK



ISDN patch panels

Number of Ports	25 and 50 x RJ45
Life Cycle	750 plug insertions
Contact Material	15 µin gold
IDC Block	Krone 4p4c and 8p8c
IDC Block Life Cycle	200 terminations
Conductor Size and Type	AWG 26 – 22, solid
Other Material	FR according to UL94-0
Colour	Black
Units	1U
Height	44 mm
Width	484 mm
Depth	129 mm
Storage Temperature	-40 to +70 °C
Operation Temperature	-10 to +60 °C
Max. Humidity Operation	93 %

Solarix ISDN Category 3 patch panels are high-density panels with 25 and 50 ports. The panels meet all electrical parameters for Category 3 and are designed for termination of two pair telecommunication cables in Krone termination blocks. Their printed circuit board design together with solid quality components ensures the Category 3 performance. Integrated back cable management for separate cables provides organized and secure installation. All ports are numbered. Solarix ISDN patch panels are available in 1U height and black colour.

Part No.

Description

SX25-ISDN-BK

19" Patch Panel Solarix ISDN 25 x RJ45 Black 1U

SX50-ISDN-BK

19" Patch Panel Solarix ISDN 50 x RJ45 Black 1U

SX50-ISDN-BK

