## **Cavity wall installation boxes**









## Two-gang junction box

- · for 2 electrical inserts or 1 block insert
- · with cover (Art. No. 9062-90), for use as a junction box
- use separator wall to separate electrical circuits Art. No. 9062-22
- · with holding ring

| Order number:  | 9062-02       |
|--|---------------|
| EAN:   | 4013456210905 |
| For panel thickness  | 7 - 40 mm     |
| Depth  | 47 mm         |
| Cut hole Ø   | 2 x 68 mm     |
| Device screws +/-  | 4             |
| Centre distance  | 71 mm         |
| Conduit entries Ø 20 mm  | 6             |
| Cable entries 3 x 2.5 mm <sup>2</sup> or 5 x 1.5 mm <sup>2</sup> | 2             |
| Cable entries 3 x 1.5 mm <sup>2</sup>                            | 4             |
| Packaging inner/dispatch   | 10/100        |

The new KAISER cavity wall installation boxes with proven mounting lug technology and improved product features. A practical design and a large selection of cable and conduit entries allow a large number of applications. Additional boxes for installation in thinly boarded walls or solid wood walls complete the wide range. VDE certification documents the high level of quality.

- · Screws ensure permanent fixing
- · Entries can be broken out for cables and conduits
- · Combinable and through-wiring by using support connectors
- · Fixing of devices by means of pre-mounted device screws













