

## Air-tight flush-mounting boxes



UPPLUS



ECON  
TECHNIK

LUFTDICHT

### One-gang junction box ECON® 15

- Air-tight design with ECON® sealing membranes
- 4 screw domes, 2 expanding claws fields
- dimensions in accordance with German DIN 49073
- For M20/M25 conduits

**Order number:** 1555-21

EAN: 4013456533318

Depth 66 mm

Screw spacing 60 mm

Tool-free cable and conduit entries in the connector area up to M25 2

Tool-free cable and conduit entries up to 11 mm below the connector 2

Tool-free cable and conduit entries up to M25 around the box 4

Tool-free cable and conduit entries up to 11 mm around the box 4

Air-tight Yes

Packaging inner/dispatch 25/250

Flush-mounting boxes with ECON® technology permit guaranteed air-tight installation. They offer a variety of options for air-tight conduit and cable entries and can be either plastered or processed using Klemmfix®. The new ECON® Multi-Membrane allows the insertion of several cables without gusset formation or the insertion of conduits up to M25.

- Air-tight design with ECON® sealing membranes
- Avoids leaks in exterior facades made from hollow chamber blocks
- Variable and tool-free cable and conduit entries
- Torsion-proof, guaranteed standardised combination distance of 71 mm

