## Box sealing system DS 90 / 120 mm











## Box sealing system DS 90 / 120 mm

- · for EI90 fire-protection walls
- · attachment using tried-and-tested FX4 metal plate screws
- with integrated sealing inserts
- · ensures smoke-tight room separation (seals against cold smoke)
- · unlimited building material shelf life

Order number:	9459-04
EAN:	4013456537156
Cut hole Ø	120 mm
Min. wall thickness	100 mm
Cable entries	Maximum population (Inner diameter 74 mm)
DIBt approval	Z-19.53-2188
for sound insulation walls up to	72 dB
Dispatch	4

The new box sealing system DS 90 / 120 mm covers an additional range of applications in building fire protection. The increased diameter makes it possible to use a larger number of cables and electrical installation conduits and also greater diameters. With this system, it is also possible to mix the installation of conduits and cables. In addition, full population, as with the DS 90 / 74 mm, allows use of the system in all fields of building technology. Because no additional materials are used, non-destructive retrofitting is also possible. The tried-and-tested screw fixing permits clean, safe and secure installation.

- · Secure, visible, certified fire sealings
- · Seals wall feed-throughs
- · Automatic sealing of the joints and gaps between cables no filling and smoothing
- · Non-destructive retrofitting
- · Also for mixed population of bundles of cables and conduits









