

# DKS 20-40 Dowel clamp 30060

CE  
7/2021

## Areas of application:

For the single installation of casing pipes (single cable and cable bundles) such as antenna cables, telephone lines and flex s.

## Installation Guide:

- Drill a 6mm Ø hole
- Wrap the DKS around the cable
- Insert the DKS into the drill hole

## Product details:

Colour	light grey
Content pack/box	200 / 4.000
Clamping range mm	20-40

## Mounting and usage instructions:

Cover the cable(s) with the DKS and insert the DKS into a 6 mm drill hole. Drill. Fasten. Done!

## Product benefits/properties:

Good cable tension options with the DKS. When laid, the strap is barely visible.

## Technical data:

Material	PP, UV stabilised Temperature range: -10 °C up to +85 °C silicon-free <b>halogen-free</b>
Weight per piece	1,20 g
Max. recd. load	Reference value: DKS 3-13: 45 N (4,5 kg) concrete, 45 N (4,5 kg) solid brick
Breaking load	Reference value: DKS 3-13: 248.00 N (24.8 kg) concrete, 271.80 N (27 kg) hollow brick
GTIN (EAN)	9 008439 300600



 **Schnabl**<sup>®</sup>  
time saving products

Schnabl Stecktechnik GmbH, Bahnhofplatz 1, po box 63, 3100 St. Pölten, Austria  
Telephone +43 2742 22167-0, office@schnabl.works, www.schnabl.works

Only the  
ORIGINAL is  
ingenious

